



# ELECTRICAL SYSTEM DESIGN AND INSTALLATION GUIDELINES FOR ARCHITECTS & ENGINEERS

## SECTION 10 : LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

Mei 2012

Oleh : JEPK, BPR (PK)  
CKE



## 10.1 Description :

- A complete system used to reduce physical damage due to lightning flashes to the structure.
- This section will identify the requirement of installation for a complete lightning protection system (LPS) to MS IEC 62305.



# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

- 3 main components of an external lightning protection system and their functions are:
  - a) Air termination system to intercept a lightning flash to the structure.
  - b) Down conductor system to conduct the lightning current safely to earth.
  - c) Earth termination system to disperse the lightning current into the earth.



## 10.2 Location :

- Not isolated from the structure to be protected. (LPS with an air termination system and down conductor system positioned in such a way that the path of the lightning current is in contact with the structure to be protected).

[\(Refer to Figure 10.1 : External Lightning Protection System\)](#)



# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

## 10.3 Physical specification :

Item	Requirement	Action
10.3.1 Air Termination System	a) Structure with non metallic roof.  (i) Air termination system shall consist of a network of vertical and horizontal conductors. The probability of structure penetration by a lightning current is considerably decreased by the presence of a properly designed air-termination system. Air termination systems can be composed by any combination of rods (including free-standing masts), catenary wires and meshed conductors.	A, C/S



# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

## 10.3 Physical specification :

Item	Requirement	Action
10.3.1 Air Termination System	(ii) Lightning conductor shall be installed at corners, exposed points and edges (especially on the upper level of any facades).	A,C/S
	(iii) Positioning of the air termination component shall be determined by using one or any combination the following method : <ul style="list-style-type: none"><li>• Protection angle method</li><li>• Rolling sphere method</li><li>• Mesh method</li></ul> <p>(<a href="#">Refer to Table 10.2</a> : Value of protection angle, rolling sphere radius and mesh size for eah class of LPS)</p>	A, C/S



# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

## 10.3 Physical specification :

Item	Requirement	Action
10.3.1 Air Termination System	<p>(iv) All metallic projections on or above the main surface of the roof of the structure shall be bonded to and form part of the air termination network.</p> <p>(v) Air termination will be run exposed along the roof and connected to the down conductors, usually at columns.</p> <p><a href="#">(Refer to Figure 10.2 : Air Termination System For Concrete/Slate Roof)</a></p>	A,M,C/S  A,M, C/S



# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

## 10.3 Physical specification :

Item	Requirement	Action
10.3.1 Air Termination System	<p><u><a href="#">(Refer to Figure 10.3 : Air Termination Network)</a></u></p> <p>(v) For structure taller than 60 meters, a lateral air termination system shall be installed on the upper part typically the topmost 20% of the height of the structure for protection against flashes to the side of the structure.</p> <p><u><a href="#">(Refer to Figure 10.4 : Air Termination Installation For Structure Higher Than 60 m)</a></u></p> <p>(vi) If there is metal facade, it must be bonded and formed part of the air termination.</p>	<p>A, C/S</p> <p>A,C/S</p>





# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

## 10.3 Physical specification :

Item	Requirement	Action
10.3.1 Air Termination System	<p>b) Structure with metallic roof</p> <p>If the structure incorporates metallic roofing, the metallic roofs can be considered as a natural air termination system provided that it meets the minimum thickness and type of material under consideration.</p> <p><u><a href="#">(Refer to Table 10.1 : Minimum Thickness of Metal Sheets/Metal Pipes in Air Termination System)</a></u></p>	A, C/S
	<p><u><a href="#">(Refer to Figure 10.5 : Air Termination System : Installation of LPS conductor on metal deck roof)</a></u></p> <p>if the metallic roof does not form part of the air termination system .</p>	A, C/S



## 10.3 Physical specification :

Item	Requirement	Action
10.3.2 Down Conductor System	<p>a) A down conductor will be installed at each exposed corner of the structure. Down conductors shall be installed straight and vertical such that they provide the shortest and most direct path to earth. The down conductors shall not be installed in gutters or down-spouts even if they are covered with insulating materials.</p> <p>(Refer to <a href="#">Table 10.3</a> – Typical values of the distance between down conductors and between ring conductors according to the class of LPS)</p> <p>b) Methods of down conductor installation:</p>	A, C/S





# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

## 10.3 Physical specification :

Item	Requirement	Action
10.3.2 Down Conductor System	<ul style="list-style-type: none"> <li>iii. Use of natural components               <ul style="list-style-type: none"> <li>- Natural components made of conductive material, which will always remain in/on the structure and will not be modified (e.g. interconnected reinforced steel, metal framework of the structure, etc.) may be used as parts of LPS.</li> <li>- Steelwork within reinforced concrete structures is considered to be electrically continuous provided that the major part of interconnections of vertical and horizontal bars are welded (over a length not less than 30mm) or otherwise securely connected (Clamps conforming to EN 50164-1 may be considered suitable)</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>A,C/S</li> <li>C/S</li> </ul>



# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

## 10.3 Physical specification :

Item	Requirement	Action
10.3.2 Down Conductor System	<p>iii. Use of natural components (cont.)</p> <ul style="list-style-type: none"><li>- Connection of vertical bars shall be welded or properly clamped or otherwise securely connected.</li><li>- The overall electrical resistance measured between the uppermost part and ground level should not be greater than <math>0.2\Omega</math>.</li></ul>	C/S



## 10.3 Physical specification :


Item	Requirement	Action
10.3.3 Earth Termination System	a) General  Down conductor shall be connected to the earth termination system consist of earthing conductor and earth electrodes. <a href="#">(Refer to Figure 10.8 : Earth Termination System)</a>	A, C/S
	b) Types of earth termination system: <u>Type A</u> - comprises of horizontal/vertical earth electrodes installed outside the structure to be protected connected to each down-conductor.	C/S





# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

Fig.10.10 : Overall Lightning Protection System







**TERIMA KASIH**



# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

Fig.10.1 : External Lightning Protection System




Example of Air Termination System



Example of Down Conductor System





Example of Earthing System





# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES


## Fig.10.2 : Air Termination System For Concrete/Slate Roof





# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

## Fig.10.3 : Air Termination Network



Example of air termination network on roof tiles(Top view)

Typical Installation at RC Flat Roof



# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

Fig.10.4 : Air Termination Installation For Structure Higher Than 60m






Fig.10.5 : Air Termination System – Installation on metal deck roof



## Fig.10.6 : Exposed Down Conductor System Installation











Fig.10.7 : Down Conductor System Installation – Encased in Concrete

				
<p>Example of Down Conductor installed through the reinforcement.</p>	<p>Example of approved connectors for connecting LPS conductors with the reinforcement.</p>	<p>Example of approved connectors for connecting LPS conductors with the reinforcement.</p>	<p>Non approved connection between earthing tape and reinforcement. The wire will not be able to withstand the lightning current causing explosion and cracks on the concrete.</p>	<p>Down conductor is driven through the reinforcement without having any bonding.</p>
	<p>[√] Good Practice</p>	<p>[√] Good Practice</p>	<p>[X] Bad Practice</p>	<p>[X] Bad Practice</p>









# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

Fig.10.8 : Earth Termination System




Example of earthing system c/w inspection chamber



# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

Fig.10.9 : Earth Termination System : Foundation Earth Electrode




Detail connection at pile electrode



# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

Fig.10.11 : Foundation earth electrode (Top view)






# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

Table 10.1 : Minimum Thickness of Metal Sheets/Metal Pipes in Air Termination System.

Material	Thickness <sup>(1)</sup> t (mm)	Thickness <sup>(2)</sup> t' (mm)
Lead	-	2.0
Steel (stainless, galvanized)	4	0.5
Titanium	4	0.5
Copper	5	0.5
Aluminum	7	0.65
Zinc	-	0.7

Notes :

- (1) Thickness t to prevents puncture, hot spot or ignition
- (2) Thickness t' only for metal sheets if it is not important to prevent puncture, hot spot or ignition problems
- (3) Electrical continuity between the various parts shall be made durable (e.g by means of brazing, welding etc)
- (4) They shall not clad with insulating material





# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES



Table 2 – Maximum values of rolling sphere radius, mesh size and protection angle corresponding to the class of LPS

Class of LPS	Protection Method		
	Rolling sphere radius $r$ m	Mesh size $W$ M	Protection angle $\alpha^\circ$
I	20	5 x 5	See figure below
II	30	10 x 10	
III	45	15 x 15	
IV	60	20 x 20	



# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

Table 2 – Maximum values of rolling sphere radius, mesh size and protection angle corresponding to the class of LPS (cont.)





# LIGHTNING PROTECTION SYSTEM FOR STRUCTURES

Table 3 – Typical values of the distance between down conductors and between ring conductors according to the class of LPS

Class of LPS	Typical Distance m
I	10
II	10
III	15
IV	20

