

TILE ADHESIVE & TILE GROUT SOLUTION AND SPECIFICATION



NO	AREAS	PRODUCT	THICKNES S	SPECIFICATION	UNIT	PRICE (RM)
1	BRICK WALL - RENDER	Ceramic wall tiles < 300 x 300 mm Weberset CTF Grey	8 - 12 mm per coat	(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing render (measured separately) as described bedded with < Weberset CTF Grey >, adhesive and jointed and pointed in < Weberfill Fine Grout / Weberfill F&W Grout > to joints and “Weber” or other equal and approved cement grout as described to match walls/floors & column.	m2	4.13 / m2 / 7.5mm thick
		Ceramic Wall Tiles > 300 x 300 mm Weberset CTF Grey	15 - 18 mm per coat			4.95 / m2 / 9mm thick
		Ceramic Mosaics Weberset CTF Grey	4 - 5 mm per coat			2.47 / m2 / 4.5mm thick
2	BRICK WALL - RENDER	Porcelain Wall Tiles <300 x 300 mm Weberset Easy Flex	8 - 12 mm per coat	(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing render (measured separately) as described bedded with < Weberset Easy Flex >, adhesive and jointed and pointed in < Weberfill Fine Grout / Weberfill F&W Grout > to joints and “Weber” or other equal and approved cement grout as described to match walls/floors & column.	m2	6.11 / m2 / 7.5mm thick
		Porcelain Wall Tiles > 300 x 300 mm Weberset Super Flex 21	15 - 18 mm per coat	(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with < Weberset Super Flex 21 >, adhesive and jointed and pointed in < Weberfill Fine Grout / Weberfill F&W Grout > to joints and “Weber” or other equal and approved cement grout as described to match walls/floors & column.		9.89 / m2 / 9mm thick
		Mosaics Weberset Superflex 21 (White/Grey)	4 - 5 mm per coat	(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with < Weberset Super Flex 21 >, adhesive and jointed and pointed in < Weberfill Fine Grout / Weberfill F&W Grout > to joints and “Weber” or other equal and approved cement grout as described to match walls/floors & column.		4.95 / m2 / 4.5mm thick

3	BRICK WALL - *EXTERNAL / SWIMMING POOL * < 3METER HEIGHT	Porcelain Wall Tiles Weberset CTF Grey + Webermix Admix 1	8 - 12 mm per coat	(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with <Weberset CTF Grey> , adhesive incorporating <Webermix Admix I> , latex admixture conforming to BS 5980 : 1980 (MS 1295 : 1992); and jointed and pointed in <Weberfill Fine Grout / Weberfill F&W Grout> to joints and “Weber” or other equal and approved cement grout as described to match walls/floors & column.	m2	23.30 / m2 / 9mm thick
		Mosaics Weberset Super Star + Webermix Admix 1	4 - 5 mm per coat	(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with <Weberset Super Star> , adhesive incorporating <Webermix Admix I> , latex admixture conforming to BS 5980 : 1980 (MS 1295 : 1992); and jointed and pointed in <Weberfill Fine Grout / Weberfill F&W Grout> to joints and “Weber” or other equal and approved cement grout as described to match walls/floors & column.		11.00 / m2 / 4.5mm thick
4	RC WALL - INTERNAL	Substrate Pretreatment	-	Reduced Water Suction & Improved bonding	m2	2.29 / m2 / coat
		Ceramic Wall Tiles Weberset Easy Flex	8 - 12 mm per coat	(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with <Weberset Easy Flex> , adhesive and jointed and pointed in <Weberfill Fine Grout / Weberfill F&W Grout> to joints and “Weber” or other equal and approved cement grout as described to match walls/floors & column.	m2	6.11 / m2 / 7.5mm thick
		Porcelain Wall Tile Weberset Super Flex 21	15 - 18 mm per coat	(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with <Weberset Super Flex 21> , adhesive and jointed and pointed in <Weberfill Fine Grout / Weberfill F&W Grout> to joints and “Weber” or other equal and approved cement grout as described to match walls/floors & column.		9.89 / m2 / 9mm thick

		<p>Porcelain Wall Tiles > 800 x 800 mm Weberset X'tra Flex</p>	<p>15 - 20 mm per coat</p>	<p>(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with <Weberset X'tra Flex>, adhesive and jointed and pointed in <Weberfill Fine Grout / Weberfill F&W Grout> to joints and "Weber" or other equal and approved cement grout as described to match walls/floors & column.</p>		<p>17.69 / m2 / 12mm thick</p>
5	RC WALL - *EXTERNAL / SWIMMING POOL * < 3METER HEIGHT	<p>Substrate Pretreatment weberprim SP1</p>	-	Reduced Water Suction & Improved bonding	m2	2.29 / m2 / coat
		<p>Ceramic Wall Tiles Weberset X'tra Flex</p>	<p>8 - 12 mm per coat</p>	<p>(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with <Weberset X'tra Flex>, adhesive and jointed and pointed in <Weberfill Fine Grout / Weberfill F&W Grout> to joints and "Weber" or other equal and approved cement grout as described to match walls/floors & column.</p>		<p>11.07 / m2 / 7.5mm thick</p>
		<p>Porcelain Wall Tile Weberset X'tra Flex</p>	<p>8 - 12 mm per coat</p>	<p>(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with <Weberset X'tra Flex>, adhesive and jointed and pointed in <Weberfill Fine Grout / Weberfill F&W Grout> to joints and "Weber" or other equal and approved cement grout as described to match walls/floors & column.</p>		<p>13.26 / m2 / 9mm thick</p>
		<p>Porcelain Wall Tiles > 800 x 800 mm Weberset Super Star + Webermix Admix 1</p>	<p>15 - 20 mm per coat</p>	<p>(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with <Weberset Super Star>, adhesive incorporating <Webermix Admix I>, latex admixture conforming to BS 5980 : 1980 (MS 1295 : 1992); and jointed and pointed in <Weberfill Fine Grout / Weberfill F&W Grout> to joints and "Weber" or other equal and approved cement grout as described to match walls/floors & column.</p>	m2	<p>36.62 / m2 / 12mm thick</p>

		<u>Mosaics</u> Weberset Super Star + Webermix Admix 1	4 - 5 mm per coat	(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with <Weberset Super Star> , adhesive incorporating <Webermix Admix I> , latex admixture conforming to BS 5980 : 1980 (MS 1295 : 1992); and jointed and pointed in <Weberfill Fine Grout / Weberfill F&W Grout> to joints and “Weber” or other equal and approved cement grout as described to match walls/floors & column.		11.00 / m2 / 4.5mm thick
6	FLOOR SCREED - INTERNAL CORRIDOR WALK WAY	<u>Ceramic Floor Tiles</u> Weberset CTF Grey	8 - 12 mm per coat	(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with <Weberset CTF Grey> , adhesive and jointed and pointed in <Weberfill Fine Grout / Weberfill F&W Grout> to joints and “Weber” or other equal and approved cement grout as described to match walls/floors & column.	m2	4.13 / m2 / 7.5mm thick
		<u>Porcelain Floor Tiles</u> Weberset Easy Flex	8 - 12 mm per coat	(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with <Weberset Easy Flex> , adhesive and jointed and pointed in <Weberfill Fine Grout / Weberfill F&W Grout> to joints and “Weber” or other equal and approved cement grout as described to match walls/floors & column.		7.32 / m2 / 9mm thick
		<u>Mosaics</u> Weberset Superflex 21 (White/Grey)	4 - 5 mm per coat	(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with <Weberset Superflex 21> , adhesive and jointed and pointed in <Weberfill Fine Grout / Weberfill F&W Grout> to joints and “Weber” or other equal and approved cement grout as described to match walls/floors & column.		4.95 / m2 / 4.5mm thick

7	FLOOR SCREED - EXTERNAL EXTERNAL FLOOR	Porcelain Floor Tiles Weberset CTF Grey + Webermix Admix 1	16 - 18 mm per coat	(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with <Weberset CTF Grey> , adhesive incorporating <Webermix Admix I> , latex admixture conforming to BS 5980 : 1980 (MS 1295 : 1992); and jointed and pointed in <Weberfill Fine Grout / Weberfill F&W Grout> to joints and “Weber” or other equal and approved cement grout as described to match walls/floors & column.	m2	23.31 / m2 / 9mm thick
		Mosaics Weberset Super Star + Webermix Admix 1	4 - 5 mm per coat	(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed / render (measured separately) as described bedded with <Weberset Super Star> , adhesive incorporating <Webermix Admix I> , latex admixture conforming to BS 5980 : 1980 (MS 1295 : 1992); and jointed and pointed in <Weberfill Fine Grout / Weberfill F&W Grout> to joints and “Weber” or other equal and approved cement grout as described to match walls/floors & column.		11.00 / m2 / 4.5mm thick
8	CEMENT-SAND SCREEDED FLOOR - INTERNAL	Porcelain Floor Tiles > 600 x 600 mm Weberset One-Fix	6 - 12 mm per coat	(Type of Ceramic / Porcelain / Homogeneous Tiles/ Mosaics Tiles) as laid to pattern on Cement Sand (1:3) backing screed (measured separately) as described bedded with <Weberset One-Fix> , adhesive and jointed and pointed in <Weberfill Fine Grout / Weberfill F&W Grout> to joints and “Weber” or other equal and approved cement grout as described to match walls/floors & column.	m2	7.99 / m2 / 9mm thick
9	TILE GROUT	Tile Grout - Standard Color Weberfill Fine Grout Weberfill F&W Grout	3mm	Coverage = Approx. 0.27kg / m2 based on 300 x 300 x 8mm tile with 3mm joints. [Approx. 75 m2 / 20kg bag]	m2	0.43 / m2
		Tile Grout - Special Color Weberfill Fine Grout Weberfill F&W Grout	3mm			0.55 / m2

	TILE GROUT	<u>Tile Grout - Standard</u> <u>Color</u> Weberfill Fine Grout Weberfill F&W Grout	3mm	Coverage = Approx. 0.17kg / m ² based on <u>600 x 600 x 10mm tile</u> with 3mm joints. [Approx. 117 m ² / 20kg bag]	m ²	0.27 / m ²
		<u>Tile Grout - Special</u> <u>Color</u> Weberfill Fine Grout Weberfill F&W Grout	3mm			0.35 / m ²