

KERAJAAN MALAYSIA

Guidelines for Presentation of Engineering Drawings

©2016 Jabatan Kerja Raya Malaysia.



Hak Cipta Terpelihara.

Tidak dibenarkan mengeluarkan mana-mana bahagian artikel, ilustrasi dan isi kandungan buku ini dalam apa jua bentuk dan dengan apa jua cara sama ada secara elektronik, mekanikal, salinan, rakaman atau cara lain sebelum mendapat keizinan bertulis daripada penerbit.

Guidelines for Presentation of
Engineering Drawings



Jabatan Kerja Raya
Cawangan Jalan



Ketua Pengarah Kerja Raya
Jabatan Kerja Raya Malaysia
Jalan Sultan Salahuddin
50582 Kuala Lumpur

PREFACE & ACKNOWLEDGEMENT

This is the second revision of Arahan Teknik (Jalan) 6/85 on *Guidelines for Presentation of Engineering Drawings*. Although it is basically similar in essence and format to both of those versions published in 1985 and 1988, various modifications have been made to suit current JKR requirements. These guidelines should be followed for the presentation of engineering drawings for all road projects under JKR Malaysia.

This Arahan Teknik (Jalan) 6/85 will continue to be updated from time to time and in this respect, any feedback regarding these guidelines will be most welcome. All comments should be sent to Cawangan Jalan, Ibu Pejabat JKR Malaysia. This guideline was prepared by a working committee comprising of the following members:

Pn. Sujatiah Bt. Tamrin (Chairperson)	- Caw. Jalan, Jabatan Kerja Raya
En. Wan Zuhaimie B. Wan Salleh	- Caw. Jalan, Jabatan Kerja Raya
Pn. Mardhiyah Syahida Bt. Berhanuddin	- Caw. Jalan, Jabatan Kerja Raya
Pn. Jamilah Bt. Atan	- Caw. Jalan, Jabatan Kerja Raya
Pn. Khadijah Bt. Basar	- Caw. Jalan, Jabatan Kerja Raya
En. Ahmad Fahmi B. Abdul Ghaffar	- Caw. Jalan, Jabatan Kerja Raya
Ir. Rohaida Bt. Rashid	- Caw. Jalan, Jabatan Kerja Raya
Pn. Roziawati Bt. Razali	- Caw. Jalan, Jabatan Kerja Raya
En. Wong Thian Chiun	- Caw. Jalan, Jabatan Kerja Raya
En. Hafiz B. Ahmad	- Caw. Jalan, Jabatan Kerja Raya
Pn. Sri Indrayani Bt. Jaafar	- Caw. Jalan, Jabatan Kerja Raya
Cik Valerie Ivy Kinsely	- Caw. Jalan, Jabatan Kerja Raya
Pn. Nor Azian Bt. Aziz	- Caw. Jalan, Jabatan Kerja Raya
Pn. Rohana Bt. Yaakub	- Caw. Jalan, Jabatan Kerja Raya
Pn. Siti Nurilam Bt. Abu Mansor	- Caw. Jalan, Jabatan Kerja Raya
Pn. Rosmawati Bt. Abdul Razak	- Caw. Jalan, Jabatan Kerja Raya
Cik Eda Fatimawati Bt. Ahmad Fuzi	- Caw. Jalan, Jabatan Kerja Raya
Ir. Shaharuddin B. Bahari @ Bahri	- Caw. Alam Sekitar & Tenaga, Jabatan Kerja Raya
Pn. Wan Rifhan Bt. Wan Ab. Rahim	- Caw. Kejuruteraan Elektrik, Jabatan Kerja Raya
Pn. Nas Naweerah Bt. Rahim	- Caw. Kejuruteraan Elektrik, Jabatan Kerja Raya
En. Chandra Mohan a/l Muthusamy	- Caw. Kejuruteraan Geoteknik, Jabatan Kerja Raya
En. Mohd Ikhwan B. Che Omar	- Caw. Kejuruteraan Geoteknik, Jabatan Kerja Raya

Special thanks and appreciation to Ir. Mohd Azahar bin Don for his effort in proof reading the document.

CONTENTS

1. INTRODUCTION	1
2. DRAWING REQUIREMENTS	1
3. SEQUENCE OF DRAWINGS	1
4. SCALES OF DRAWINGS	2
5. SEQUENCE AND SCALES OF TENDER DRAWINGS	2
6. CONTENTS OF DRAWINGS	3
6.1 Cover or Title Page	3
6.2 Drawing Index	3
6.3 Key Plan	3
6.4 Location Plan	4
6.5 Abbreviation, Symbol and Legend Plan	4
6.6 Elements of Curve Plan	4
6.7 Superelevation Detail Plan	5
6.8 Typical Road Cross Section and Pavement Details Plan	5
6.9 Alignment Control Plan	6
6.10 Plan and Longitudinal Profile Plan	7
6.11 Cross Section Plan	8
6.12 Junction Detail Plan	9
6.13 Road Marking Plan	9
6.14 Traffic, Guide and Temporary Sign Plan	10
6.15 Drainage Plan	10
6.16 Traffic Management Plan	10
6.17 Structure Plan	11
6.18 Protection and Relocation of Services Plan	16
6.19 Electrical Plan	16
6.20 Environmental Protection Works Plan	18
6.21 Geotechnical Plan	19
7. DRAWING NUMBERING SYSTEM	21

1. **INTRODUCTION**

The following guidelines have been prepared in order to standardise the presentation of engineering design drawings for road projects undertaken by JKR and which has complied to the relevant standards and requirements.

The objectives of setting these guidelines are:-

- (a) to maintain a consistent standard in the production of engineering drawings that will clearly and concisely describe the works to be carried out;
- (b) to simplify the draughting process, the checking of drawings and where possible reduce the draughting requirements without detracting from the completeness of the works;
- (c) to produce drawings that can be readily modified with a minimum of redrafting to provide complete “as constructed” records for the project.

These guidelines have been compiled by incorporating the good features of design drawings prepared by JKR and those submitted by Consultants.

2. **DRAWINGS REQUIREMENT**

All drawings (master tracings) are to be A1 size 594mm, by 841mm with a 10mm, 12mm and 21mm border. There are several types of title block format as shown in Model Drawings No. 1A to 1D as below:

- i) Drawing No. 1A – Title block format for standard drawing
- ii) Drawing No. 1B – Title block format for design & build
- iii) Drawing No. 1C – Title block format for in-house design
- iv) Drawing No. 1D – Title block format for consultant design

General notes and legends are to be located on the right hand side of the title block.

Drawings shall be arranged so that the Northing Arrow is at the top right hand corner of the drawing. No other type of Northing Arrow is allowed.

All drawings submitted (including draft copies) must have Professional Engineer's (P.E.) chop and signature of at least a director of the consulting engineer's firm.

3. **SEQUENCE OF DRAWINGS**

Engineering data shall be prepared in a logical method starting from general information and scope of works to increasingly specific details or items and method of work. The recommended sequence for the Drawings is set out in Section 5.

4. **SCALES OF DRAWING**

The scales of drawings shall be selected to clearly illustrate the information that is to be relayed. Generally, to show more details, larger scales of drawing and greater number of drawings are required. However, the smaller the scale, the more limited the designer is in relaying the complete information on one drawing. Accordingly, information may have to be disaggregated so that one drawing may be limited to one subject at a time.

All scales are to be in metric system except for Land Acquisition Plans which have to be in accordance to the respective Land Office's requirement.

5. **SEQUENCE AND SCALES OF DRAWINGS**

5.1 The following illustrates the sequence of Tender Drawings and scales that are to be used in a typical road project:-

<u>Drawing Title</u>	<u>Scale</u>
(a) cover or title page	not applicable
(b) list of drawings	not applicable
(c) key plan	not applicable
(d) location plan	not applicable
(e) abbreviation, symbol and legend plan	not applicable
(f) elements of curve plan	not applicable
(g) superelevation details plan	not applicable
(h) typical road cross sections and pavement details plan	suitable scale
(i) alignment control plan	1:1,000 to 1:6,000
(j) plan and longitudinal profile plan	Horizontal 1:1,000 Vertical 1:100
(k) cross section plan	1:500 (recommended)
(l) junction details plan	1:500 or 1:750
(m) traffic control plan	1:1,000
(n) traffic management plans	1:1,000
(o) drainage plan	1:1,000
(p) structure plan	stated in section 6.17
(q) protection and relocation of services plan	1:1,000
(r) environmental plan	1:1,000
(s) geotechnical plan	stated in section 6.21 & model of drawings
(t) road lighting plan	1:1,000

- 5.2 Land Acquisition plans will not form part of the Tender Drawings but have to be prepared for the purposes of Land Acquisition. The scale will be as that required by the Land Office, usually 1 inch to 4 chains or 8 chains. The details are given in JKR publication— “GARIS PANDUAN UNTUK PENYEDIAAN PELAN PENGAMBILAN BALIK TANAH BAGI PROJEK JALAN PERSEKUTUAN - ARAHAN TEKNIK (JALAN) 7/85 (PINDAAN 2014)”. However, all matters relating to the acquisition of land must comply with the requirements set by the Land Office.

6. **CONTENTS OF DRAWINGS**

6.1 **Cover or Title Page**

The cover or title page shall follow Model Drawing No. 2A.

6.2 **Drawing Index**

This drawing lists all the titles and number of each drawing within the List of Contract Drawings. Please refer to Model Drawing No. 3A for guidance. A Drawing Numbering System has been drawn up and all drawings must follow this system. For all projects, whether designed departmentally or by Consultants, the project number must be obtained from the Documentation Unit. Please refer to Section 7 for full explanation of the system.

6.3 **Key Plan**

This drawing shall indicate:-

- (a) project location with respect to other states in the country;
- (b) state boundaries;
- (c) name of states and main towns where the project is located;
- (d) all the major Federal Routes;
- (e) northing arrow;
- (f) suitable scales - 1:2,000,000 to 1:3,000,000

The key plan can be combined with the location plan.

Please refer to Model Drawings No. 4A and 4B for guidance.

6.4 Location Plan

This drawing shows: -

- (a) specific location of the project with respect to the surrounding areas, limit of project and kilometre post.
- (b) the proposed alignment;
- (c) other projects in the vicinity if any;
- (d) local towns, villages, rivers, reservoirs, roads, railway tracks and other physical features, etc;
- (e) route number;
- (f) northing arrow;
- (g) suitable scales - 1:250,000

Please refer to Model Drawings No. 4A and 4B for guidance.

6.5 Abbreviation, Symbol and Legend Plan

This drawing shall contain:-

- (a) abbreviations, symbol and legends and their corresponding full words, details and representations.

The abbreviations, symbols and legends are standardised and shall not be changed.

Please refer to the Standard Drawings for guidance.

6.6 Elements of Curve Plan

This plan shall indicate the following:-

- (a) typical horizontal curves' transitions; with or without transition;
- (b) typical vertical curve - parabolic curve;
- (c) clothoid formulae or other formulae used and their notations.

Please refer to the Standard Drawings for guidance.

6.7 Superelevation Details Plan

This plan shall contain the following:-

- (a) superelevation for curves with or without transition;
- (b) superelevation for the single carriageway and where applicable, dual carriageway too;
- (c) typical shoulder treatment on superelevation.

Please refer to the Standard Drawings for guidance.

6.8 Typical Road Cross Section and Pavement Details Plan

This drawing shall indicate the following:-

- (a) typical road cross section in embankment and cutting (for both flat and rolling terrain where applicable) showing width of carriageway, shoulders, camber, drainage features, etc;
- (b) superelevated typical cross sections where applicable;
- (c) typical cross sections for urban, rural carriageway with drainage details and access road, if applicable;
- (d) typical cross section for ground treatment (where applicable)
- (e) section details of pavement including details for the construction of new pavement over the existing pavement (where applicable);
- (f) pavement design details such as design period, cumulative total equivalent standard axles, base year, and design subgrade CBR;
- (g) concrete parameter details such as construction joints, contraction, reinforcement, etc.

6.8.1 Pavement Rehabilitation Detail

- (a) Location of pavement rehabilitation method according to actual design

Please refer to Model Drawings No. 5A, 5B and 5C & the Standard Drawings for guidance.

6.9 Alignment Control Plan

This drawing is to indicate the bearings and distances of the various Intersection Points (I.P.'s) together with the details of the horizontal curves and I.P. points. The details shall include the following:-

- (a) points of limit of project and horizontal alignment indicated by all the I.P. points;
- (b) co-ordinates of all the I.P. points including the starting and finishing points, distances and bearing between all I.P. points in a table form;
- (c) horizontal curve data for all I.P. points;
- (d) location and chainages of all ST and TS points;
- (e) location and chainages of all SC and CS points
- (f) temporary bench marks with their levels;
- (g) all relevant Survey Department's bench marks with their levels;
- (h) all relevant references to boundary stone in setting out the first intersection point shall be indicated;
- (i) northing arrow;
- (j) suitable scales - 1:1,000 to 1:6,000.

More than one section of the horizontal alignment can be shown on the same plan using separator lines but the northing arrow shall be indicated for each section.

Please refer to Model Drawing No. 6A for guidance.

6.10 Plan and Longitudinal Profile Plan

6.10.1 Plan Profile

The details shall include the following:-

- (a) horizontal alignment of centreline together with the limits of carriageway and shoulder;
- (b) extent of R.O.W. to be acquired;
- (c) running chainages (with 25 m interval or as required) along the centreline;
- (d) extent of cut and fill areas and carriageway in distinct shades;
- (e) location of any proposed culverts and its details (including catchments area and discharge figures) and any proposed stream deviation;
- (f) location of all structures such as bridges and box culverts and their levels;
- (g) locations of boreholes, temporary bench marks, bench marks and their levels;
- (h) physical features such as existing roads, paths, tracks, public utilities etc. and contour lines;
- (i) vegetation of the area passed through, such as rubber estate, paddy fields, swamps, etc.;
- (j) existing buildings, property lines and types of buildings;
- (k) match lines;
- (l) existing stream, rivers (with names), culverts, sumps, side drains etc., their flow directions and levels;
- (m) lot numbers and boundaries the proposed alignment passes through;
- (n) northing arrow;
- (o) scale - 1:1,000.

6.10.2 Longitudinal Profile

The presentation shall be on graphical format and shall include the following details:

- (a) running chainages as per the horizontal alignment;
- (b) existing ground and proposed finished levels;
- (c) profile of existing ground and the proposed vertical alignment with the gradients;
- (d) details of vertical intersection points, including the chainage and data on the vertical curve. Locations of the BVC and EVC are to be indicated too;
- (e) locations of all proposed culverts, side drains and structures;
- (f) details of the superelevation and the horizontal alignment along a linear scale is to be provided;
- (g) scale - 1:100 or 1:200

Please refer to Model Drawing No. 7A for guidance.

6.11 Cross Section Plan

This plan shall show the cross sections of the proposed road at 25 m interval or as required along the horizontal alignment. The details shall include:-

- (a) the existing ground's sectional profile;
- (b) the proposed finished cross section indicating the extent and shape of cut and fill required;
- (c) the proposed finished road level at the centreline;
- (d) the proposed offsets and level
- (e) the crossfall or superelevation of the carriageway (optional);
- (f) any other details deemed useful for clarity;
- (g) suitable scales - 1:100 or 1:200 (recommended).

Please refer to Model Drawing No. 8A for guidance.

6.12 Junction Details Plan

6.12.1 Junction details shall include the following:

- (a) general layout plan showing details of carriageway widths, islands, limit of R.O.W., property lots, dwellings and its type, limit of project on minor roads, etc. The shoulder shall be shaded for better visual impact.
- (b) setting out plan with sufficient details so as to enable the setting out of the junction;
- (c) drainage and kerb details of the junction showing proposed type and position of drains and kerbs, culverts, etc. Proposed superelevations of various pavement and longitudinal sections can also be indicated;
- (d) road marking and traffic sign plan showing the type and positions of the proposed road markings, traffic signs and signals (if applicable).
- (e) suitable scales - 1:250 or 1:500.

Please refer to Model Drawings No. 9A, 9B and 9C for guidance.

6.12.2 Traffic signal details shall include the location of the traffic signal posts, the type of lantern and the proposed cycle times.

Schematic plans showing the various phases shall also be included.

6.13 Road Marking Plan

The plan shall show all details of the proposed lanes and pavement markings for the centerline, edge line, continuity line, chevron, give way marking, stop line, pavement direction arrows, etc.

All dimensions and details shall follow those given in JKR publication "MANUAL ON TRAFFIC CONTROL DEVICES – ROAD MARKINGS : ARAHAN TEKNIK(JALAN) 2D/85".

Please refer to Model Drawing No. 10A for guidance.

6.14 Traffic, Guide and Temporary Sign Plan

Adequate traffic guide and temporary signs shall be proposed and shall follow those approved for use by the Department.

The details are given in JKR publication “MANUAL ON TRAFFIC CONTROL DEVICES AND STANDARD TRAFFIC SIGNS - ARAHAN TEKNIK (JALAN) 2A/85 AND 2B/85”, “MANUAL ON TRAFFIC CONTROL DEVICES - TEMPORARY SIGNS AND WORK ZONES CONTROL - ARAHAN TEKNIK (JALAN) 2C/85” and “GUIDE SIGNS DESIGN AND APPLICATION - ARAHAN TEKNIK (JALAN) 2E/87”.

Please refer to Model Drawings No. 10A & Standard Drawings for guidance.

6.15 Drainage Plan

The drainage plans shall be sufficient enough to depict all details pertaining to drainage matters and shall include the following :

- (a) details of interceptor drain, bench drain, roadside drain, shoulder drain, berm drain, toe drain, outfall drain, subsoil drain, etc;
- (b) details of precast concrete slab, kerb, kerb inlet, catch pit, sump, stream deviation, piling (if needed), etc;
- (c) details of culverts (whether reinforced concrete pipe or box) with details of headwall and wingwalls, including inlet and outlet treatments.
- (d) all proposed drains shall indicate directions of flow with their types, invert levels and gradients to final discharge points.
- (e) a culvert schedule with the relevant particulars as per standard drawing.

Please refer to Model Drawing No. 11A for guidance.

6.16 Traffic Management Plan

Traffic Management Plan details shall include and indicate, but not limited to, the following:

- (a) stage of construction in plan view
- (b) lane width and number of lanes
- (c) cross Section

- (d) types of barriers used, with notes relating to appropriateness of installation and application of traffic barriers; e.g. interlocking and filled with water/sand for plastic NJB and concrete barriers used at excavation works more than 1m depth.
- (e) speed at work zone area (speed limit and advisory)
- (f) adequate and appropriate temporary sign plans. Please refer to item 6.14 for details.
- (g) engineering notes which apply to the overall traffic management plan.

Please refer to Model Drawings No. 12A, 12B, 12C, and 12D for guidance.

6.17 Structure Plans

This drawing shall normally be applied to bridge structures:-

6.17.1 Bridge Structural Plans

- (a) The general arrangement and layout shall include the following:
 - i) Location plan indicating the specific location of the bridge project with the proposed alignment, local town, villages, rivers, roads, railway tracks and other physical and geographical features. This shall include the latitude and longitude bearings, coordinates, spot levels, contours, individual land lots and the northing arrow (scale 1:10,000).
 - ii) Plan showing horizontal alignment of the centreline complete with limits of carriageway, borehole locations, direction of flow, bench marks, physical features such as public utilities, slope protection, drainage behind abutment, etc. Pile layout can also be included here.

Longitudinal profile showing running chainage as per horizontal alignment, existing ground and the proposed levels, extent of cut and fill, lower soffit level (LSL), high water level (HWL), normal water level (NWL) and limits of work for bridge construction.

- iii) Detailed cross section showing arrangement of beams and girders in typical section and other deck details.
- iv) Notes, legends, etc., which shall include the design criteria, relevant codes used and other useful information.

(b) Soil Profile

This shall include the borehole details e.g. SPT values, at various depths till end of boring. Other laboratory test results such as plasticity index, plastic limit and liquid limit shall also be incorporated if available.

(c) Piles

This shall include pile details and joints. The numbers and types of piles for abutment and piers and their capacities and estimated lengths shall be tabulated. For bored piles, the length of permanent or temporary casing and the required embedded length in hard soil (SPT >50) or the required socketed length in rock shall also be tabulated. The minimum length of concrete overfill is to be shown on the drawing. The notes shall include the materials, type of piles, (e.g. frictional or end bearing), working loads, test loads and other relevant information.

(d) Abutment and Wingwall Details

These shall include typical cross section, elevation and skew angles if any, showing details for bearings, pile layout showing principal dimensions and descriptions of all structural components. The notes shall normally include the required concrete strength, cover, etc.

A separate drawing showing reinforcement details shall be prepared with proper legends and notes.

(e) Piers

Similar requirements as for abutments.

(f) Beams

These shall include sectional drawings at the end and midspan, longitudinal and plan details indicating all dimensions and cable profiles. The reinforcement and end block details may be on the same or different drawings.

The notes shall include, among others, the design criteria, stages and sequence of stressing, jacking forces, brief material specifications, etc.

(g) Precast Segment

These shall include sectional, longitudinal and plan details indicating all dimensions. The horizontal and vertical cable profiles and the reinforcements are to be shown on separate drawings.

Separate drawings also to be provided showing the sequence of construction. These shall clearly indicate the sequence of activities at every stage of construction.

The notes shall include precamber monitoring and the design loads during construction (e.g. weight of form traveler, formwork, temporary works, construction live loads etc.).

(h) Diaphragms

These may be included in the drawings for beams, or drawings for abutments for integral bridges, or together with details of deck slab.

(i) Deck Slabs

These shall include plan and sectional details and reinforcement detail complete with relevant notes.

(j) Bearings

These shall include plan and sectional details showing the bedding and all dimensions and crossfalls, if any. The material properties (e.g. compressive and shear stiffness) and design capacity (e.g. vertical, transverse and longitudinal load, movements, rotation, etc.) is to be tabulated. Installation requirements and other relevant notes to be provided when necessary.

(k) Handrails/Parapet and Expansion Joints

These shall include plan, elevation and sectional details complete with relevant notes on material properties and installation requirements.

(l) Other Miscellaneous Details

Similar requirement as for item of New Jersey Barrier (NJB), guardrail, brass plaque, culvert marker and other miscellaneous details.

6.17.2 Culvert (3.0m and above)

The culvert (3.0m and above) plan shall be sufficient to depict all details pertaining to drain matters and shall include the following :-

- (a) general arrangement and layout shall follow as per bridge structure plan;
- (b) details of bedding or concrete slab, inlet & outlet structure, sump, stream deviation, piling (if needed), etc;
- (c) all proposed culverts (3.0m and above) shall indicate direction of flow with the invert levels and gradients;
- (d) details of culverts (3.0m and above) with details of headwall and wingwalls, including inlet and outlet structure.

6.17.3 Temporary Diversion/Crossing

(a) Temporary Diversion

The drawings for temporary road diversion shall be shown on the general arrangement drawing, showing the proposed location of the temporary diversion, the width of the temporary road diversion and also the width and span of the temporary bridge.

(b) Temporary Crossing

A separate drawing for temporary crossing shall be prepared for the details of the proposed temporary crossing, i.e. steel bridge, culvert, etc. showing all the relevant details for the proposed construction of the temporary crossing.

(c) Typical Temporary Traffic Control Devices & Signs

This drawing shall show the location of temporary road signages, barricades, temporary lightings, delineators, etc. in accordance with Arahan Teknik (Jalan) 2C/85 – “Manual on Traffic Control Devices – Temporary Signs and Work Zones Control.”

6.17.4 Bridge Construction Method / Construction Sequence

The construction sequence used in the design shall be shown on the design drawings when the construction method and sequencing is incorporated into all its design processes.

6.17.5 Sequence and Scales for Bridge Structures

The following illustrates the sequence of drawings and scales that are to be used for a typical bridge structure:

	<u>Drawing Title</u>	<u>Scale</u>
(a)	general layout	1:100, 1:150, 1:200, 1:300
(b)	soil profile	suitable scale
(c)	pile details	1:5, 1:10, 1:20, 1:50
(d)	abutment - concrete details abutment - reinforcement details	1:20, 1:25, 1:30, 1:40, 1:50
(e)	pier - concrete details pier - reinforcement details	1:20, 1:25, 1:30, 1:40, 1:50
(f)	beams and diaphragms	1:5, 1:10, 1:20, 1:25, 1:30, 1:40
(g)	deck slab details	1:20, 1:25, 1:50, 1:100
(h)	handrails/parapet and expansion joints	1:5, 1:20

6.17.6 Requirement for Dimension

A typical requirement for dimension is shown below:

- (a) all dimensions shall be expressed in metres or millimetres.
- (b) units abbreviation shall be 'm' for metre and 'mm' for millimetres. Abbreviation shall always be given in description notes but not for normal dimensioning.
- (c) normal dimensions of more than one metre shall be to three decimal places but with the point omitted.
- (d) descriptive dimensions of more than one metre shall be written to three decimal places and unit abbreviation 'm' included. Thus, for normal water, level is written as such :- NWL 37.128m.

- (e) dimensions expressed in millimetre shall be in whole numbers.
- (f) dimension shall be written to be read from the bottom or right handside of the drawing.

Please refer to Model Drawings No. 13A, 13B and 13C for guidance.

6.18 Protection and Relocation of Services Plan

This plans shall show detail for the relocation of :-

- (a) water mains;
- (b) electrical posts and cables;
- (c) telecommunication posts and cables;
- (d) gas pipes
- (e) sewerage lines
- (f) others

The drawings shall show sufficient details to properly define the scope of works. They shall show the locations, sizes, types and quantities of the existing services and their proposed relocations. All design of protection and relocation of services shall be approved by the relevant authorities.

Please refer to Model Drawing No. 14A for guidance.

6.19 Electrical Plan

The numbering system for Electrical Plan shall be as follows:

- (a) if electrical work is packaged into the main contract, the numbering system for Electrical Plan shall follow that of the main contract.
- (b) if electrical work is separately tendered (NSC),- the Key and Site/Location Plan drawings shall remain. Numbering system for Electrical Plan shall be referred to *Cawangan Kejuruteraan Elektrik, JKR Malaysia*.

The Electrical Plan shall consist of the following items :-

	<u>Items</u>	<u>References</u>
i)	cover or title page	Model Drawing No. 15A
ii)	list of electrical plan	Model Drawing No. 15B
iii)	strip map showing significant landmarks (i.e: river, bridge, substation, etc) complete with limit of works and showing scope of electrical works	Model Drawing No. 15C
iv)	design criteria that indicates : - class of road, list of standards referred to in designing, type of light source, type of column, lighting class & parameters	Model Drawing No. 15D
v)	proposed block diagram of electrical distribution system. The block diagram shall have the endorsement from local utility supplier (TNB, SESB, SESCO, etc)	Model Drawing No. 15E
vi)	the dimensioned general arrangements, layout and positions of columns and luminaires, feeder pillars, cable routes (including crossing, circuit numbers and legend) and all others necessary for the complete road lighting installation	Model Drawings No. 15F and 15G
vii)	the schematic drawings of feeder pillar	Model Drawing No. 15H
viii)	typical cross-section of the road indicating road lighting's placement	Model Drawing No. 15I
ix)	corbel and pit details at bridge parapet (if required)	Model Drawing No. 15J
x)	the layout and location of traffic light poles, traffic light controllers, cable routes (including crossing & pits), phasing, arrangement of traffic light aspects and all others necessary for the complete traffic light installation.	Model Drawing No. 15K

Traffic light system design based on timing and phasing assessment from *Bahagian Penilaian Kesan Trafik, Cawangan Jalan, JKR Malaysia*.

- xi) the schematic drawings of traffic light controller Model Drawing No. 15L

6.20 Environmental Protection Works Plan

Adequate and appropriate mitigation measures shall be proposed for the Environmental Protection Works.

The requirement for adherence to environmental protection work procedures shall be done accordingly as specified, in reference to the ARAHAN TEKNIK JALAN 16/03 (*Pindaan* 2015) - "A PRACTICAL GUIDE FOR ENVIRONMENTAL PROTECTION & ENHANCEMENT WORKS", such as :

- (a) containment bund for skid tank.
- (b) silt trap.
- (c) wash trough for construction site at urban area.
- (d) wash trough for construction site at rural area.
- (e) silt fence.
- (f) check dam.
- (g) schedule waste storage shed.
- (h) disposal of suitable cut material
- (i) silt curtain
- (j) unsuitable material disposal embankment.

All the drawings listed can be redesigned if necessary, depending on the needs of the site condition. The new design shall be sufficient and comply with current engineering requirements. The drawings shall show all the details including the locations for the proposed measures to be taken.

Please refer to Model Drawings No. 16A for guidance.

6.21 Geotechnical Plan

All drawings, tables, depth, length, height, spacing, duration, notes and other notations shown are as guidelines only. It is subjected to the changes made by the designer on the current design which will be shown in the detail drawings. The geotechnical drawings shall include the following :

6.21.1 Ground Treatment Schedule

The proposed geotechnical treatment shall be summarized in table form indicating location , type and details of ground treatment.

Please refer to Model Drawing No. 17A for guidance.

6.21.2 Location of Soil Profile on Plan and Longitudinal Profile

- (a) The proposed location of soil investigation (i.e. Bore Holes, Mackintosh Probe, Piezocone, Hand Auger) shall indicate in coordinate location (X, Y), soil investigation legend in drawing scale of 1:1000.
- (b) The chainage, reduced level and sub-surface profiles based on the S.I. report shall be indicated clearly in the longitudinal profile.
- (c) Any confirmatory soil investigation (if required) for verification of soil condition to be carried out during construction shall be specified clearly in the drawing. (e.g., BH 1A)
- (d) S.I legend and SPT guide for consistency, cohesive and non-cohesive soils shall be shown in the drawing.
- (e) Location of proposed geotechnical works along the road alignment shall be indicated in the drawings. Chainages shall be clearly shown along the road alignment.
- (f) Different types of treatment shall be clearly shown in the drawings.
- (g) JKR Probe or Mackintosh Probe recorded shall be shown in graph format, i.e. number of blows against depth.
- (h) JKR Probe or Mackintosh Probe shall be indicated as JP and MP respectively in the drawings.

Please refer to Model Drawing No. 17B for guidance.

6.21.3 Typical Details of Ground Treatment

- (a) All ground treatment, indicating chainage, embankment height, and maximum depth of excavation, type of treatment, proposed treatments and remarks shall be shown in table form.
- (b) Use number to categorize the type of soil treatment (e.g., Treatment Type 1), and letters for details (i.e., Detail A).
- (c) Slope of embankment shall be 1 : 2 and not exceeding 6 berms and extent of treatment shall be clearly shown in the drawings.
- (d) Benching details must be shown for road widening works.
- (e) Non-woven separator and high strength geotextiles should be clearly shown in the drawings.
- (f) The distance between the layers and its wrapping must be specified in the drawing.
- (g) Drainage sand blanket shall be 500mm thick with sand and extent of treatment shall be clearly shown in the drawings.
- (h) PVD specified shall indicate clearly the spacing, length and its pattern group.
- (i) The completed PVD shall be cut off nearly 300mm above the working platforms or as otherwise specified in the Contract Drawings.
- (j) Pile embankment treatment shall indicate pile spacing, working load, pile length, the length and width of pile embankment.
- (k) Slab with concrete Grade 40 or higher for project site near the coastal areas and exposed to sea tides or sulphate attack.
- (l) Transition slab interfacing between pile embankment and the road shall be within the allowable differential settlement and shown clearly in the drawing.

Please refer to Model Drawing No. 17C for guidance.

6.21.4 Instrumentation

Details of instrumentation, if any, shall include types of instruments, tentative location of instruments to be used, their duration and frequency.

Please refer to Model Drawing No. 17D for guidance.

7. **DRAWING NUMBERING SYSTEM**

7.1 The system used is as follows:-

KPKR/J/R/_____/_____/_____
1 2 3 4 5 6 7 8 9 10 11

- (a) i) KPKR stands for Ketua Pengarah Kerja Raya;
ii) J stands for Jalan;
iii) R stands for Rekabentuk.

(b) The first six spaces is to be filled by six digits.

- i) The first two digits (1st and 2nd spaces) indicate the State Code which shall be the same as those used by the JKR Headquarters Computer Centre. They are as follows:-

01	Johor
02	Kedah
03	Kelantan
04	Melaka
05	Negeri Sembilan
06	Pahang
07	Perak
08	Perlis
09	Pulau Pinang
10	Sabah
11	Sarawak
12	Selangor
13	Terengganu
14	Wilayah Persekutuan Kuala Lumpur
15	Wilayah Persekutuan Putrajaya
16	Wilayah Persekutuan Labuan

- ii) The second two digits (3rd and 4th spaces) indicate the year the project was approved for design.
- iii) The third two digits (5th and 6th spaces) indicate the series of the projects.
- (c) The seventh space is to be filled up by a numeral which represents section component of a project. To standardise, numeral in the form of 1, 2, 3, etc. is used. Each numeral will represent a section of the project or component in a package deal project. This space will be 0 (zero) if there is no component within the project.
- (d) The eighth space is to be filled up by capital alphabets A, B, C, D, etc. referring to components within the project package, if there are any.
- (e) The ninth space is to be filled up by two capital alphabets representing each category of details as follows:
 - i) AM *umum*; represents general, which includes list of drawings, key and location plan, general layout, abbreviation, symbol and legend, element of curve, superelevation, guardrail, site office, all typical drawings, etc.
 - ii) KB *keratan membujur*; represents alignment control, plan and longitudinal profile plan.
 - iii) KL *keratan melintang*; represents cross section plan.
 - iv) LP *lukisan persimpangan*; represents junction layout plan, junction setting out plan, junction drainage and pavement superelevation details plan, junction road markings, traffic signs, traffic light, etc.
 - v) KT *kawalan trafik*; represents traffic control plans including road markings, traffic signs, guide signs, temporary signs, etc.
 - vi) PP *pelan perparitan*; represents drainage plans including subsoil drain, drains, culverts, etc.
 - vii) ST *struktur*; represents structural plans including bridges, flyovers, grade-separated interchange, retaining walls, etc.
 - viii) PU *pelan utiliti*; represents public utilities and relocation of service plans.

- ix) AS *alam sekitar*; represents environmental protection works plans.
- x) PG *pelan geoteknik*; represents geotechnical plans, soil investigation, subsoil profile, etc.
- xi) PE *pelan elektrik*; represents electrical plans, road lighting, traffic light, etc.
- xii) PT *pelan tanah*; represents land acquisition plans.

- (f) The tenth space is for the series of drawings for the particular detail as described in 7.1 (e). This space will be changed accordingly if there are more than one number of intersection or structures in a project. For example, ST 1/1, ST 1 stands for structure No.1 and /1 for the series of drawings for structure No.1. For the first time of correction, it will be ST1/1A.
- (g) The eleventh space with capital alphabets in sequence shall be used for the amendments of drawings; for example, 10C for third time of correction of the same drawing.

7.2 The system shall be used for all projects including all departmental and consultant designs. The recording of serial numbers of projects will be registered by the Cawangan Kontrak Ukur dan Bahan, Ibu Pejabat JKR, Kuala Lumpur.

For JKR Internal Use Only

810.0

TITLE BLOCK FORMAT FOR STANDARD DRAWING

570.0

For JKR Internal Use Only

NOTA:
NAMA CAWANGAN (HODT) YANG BERKAITAN DENGAN SKOP KERJA BERIKUT:

- 1. CAWANGAN JALAN
- 2. CAWANGAN KEJURUTERAAN GEOTEKNIK
- 3. CAWANGAN KEJURUTERAAN ELEKTRIK
- 4. CAWANGAN ALAM SEKITAR & TENAGA

40.0	250.0	40.0	30.0	105.0	75.0	160.0	110.0
Tarikh	Butiran	Rujukan	10.0	15.5	25.0	JABATAN KERJA RAYA MALAYSIA	SAYA DENGAN INI TELAH MENYEMAK DAN MENGESAHKAN BAHAWA LUKISAN PIAWAI INI BOLEH DIGUNAPAKAI KE ATAS PROJEK BERKENAAN
			29.0	52.5	(NAMA PENUH & TANDATANGAN) PENGARAH	TAJUK LUKISAN	TANDATANGAN:
			11.0	DISEMAK OLEH:	(NAMA PENUH & TANDATANGAN) KETUA PENOLONG PENGARAH KANAN	45.0 85.0 30.0	NAMA:
	PINDAAN	UKURAN	11.5	DILULUSKAN OLEH:		TARIKH: BIL. LUKISAN : KPR/J/R/STD AM	JAWATAN:
			11.5			BIL. HELAIAN:	

TITLE BLOCK FORMAT FOR DESIGN & BUILD

- 1) Bilangan lukisan perlu didapati daripada pihak HOPT Cawangan Jalan.
- 2) Susunatur lukisan perlu merujuk kepada Standard Drawings For Road Construction dan contoh List of Drawings yang disertakan.

NOTA :
Hendaklah ditandatangani oleh Pengarah Syarikat Perunding yang bertauliah dalam bidang berkaitan.

NOTA :
KEMENTERIAN KERJA RAYA/
LAIN- LAIN KEMENTERIAN/JABATAN

P.E STAMP & SIGNATURE
I PROFESSIONAL ENGINEER (REG. NO.) HEREBY CONFIRM THAT THE DESIGNS SHOWN IN THIS CALCULATIONS/DRAWINGS/SPECIFICATIONS WAS DESIGNED BY ME OR UNDER MY DIRECTION AND SUPERVISION AND TO THE BEST OF MY KNOWLEDGE, COMPLY WITH THE RELEVANT ENGINEERING STANDARDS AND CODES OF PRACTICE, AND LOCAL AUTHORITIES BY LAW AND REGULATIONS.

NAMA PELANGGAN

TARIKH	BUTIRAN	RUJUKAN	KONTRAKTOR:NAMA & ALAMAT			CAWANGAN JALAN			JABATAN KERJA RAYA MALAYSIA		KEMENTERIAN KERJA RAYA MALAYSIA			
			JURUUKUR NAMA & ALAMAT	PERUNDING NAMA & ALAMAT	JURUAUDIT / INDEPENDENT CHECKER	NAMA PENGARAH KANAN				TAJUK PROJEK : TAJUK LUKISAN :				
					NAMA									
					JURUAUDIT KESELAMATAN JALAN	NAMA PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN				TARIKH:			BIL. LUKISAN: KPKR/J/R/	BIL. HELAIAN
					NAMA INDEPENDENT CHECKER (STRUKTUR)	NAMA KETUA PENOLONG PENGARAH KANAN (HOPT)								
PINDAAN			UKURAN	DIREKABENTUK: NAMA	DILUKIS: NAMA									
				DISEMAK: NAMA	DILULUSKAN: NAMA									
					NAMA INDEPENDENT CHECKER (GEOTEKNIK)									

TITLE BLOCK FORMAT FOR IN-HOUSE DESIGN

- 1) Bilangan lukisan perlu didapati daripada pihak HOPT Cawangan Jalan.
- 2) Susunatur lukisan perlu merujuk kepada Standard Drawings For Road Construction dan contoh List of Drawings yang disertakan.

NOTA:
KEMENTERIAN KERJA RAYA/
LAIN- LAIN KEMENTERIAN/JABATAN

NOTA:
NAMA CAWANGAN (HODT) YANG BERKAITAN DENGAN SKOP KERJA BERIKUT:

1. CAWANGAN JALAN
2. CAWANGAN KEJURUTERAAN GEOTEKNIK
3. CAWANGAN KEJURUTERAAN ELEKTRIK
4. CAWANGAN ALAM SEKITAR & TENAGA

TARIKH	BUTIRAN	RUJUKAN	JURUKUR NAMA & ALAMAT	CAWANGAN JALAN			 JABATAN KERJA RAYA MALAYSIA	 KEMENTERIAN KERJA RAYA MALAYSIA	
				NAMA PENGARAH KANAN					
				NAMA PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN					
				NAMA KETUA PENOLONG PENGARAH KANAN (HODT)					
PINDAAN			UKURAN	JURUAUDIT	NAMA KETUA PENOLONG PENGARAH KANAN (HOPT)		TAJUK PROJEK : TAJUK LUKISAN :		
				BAHAGIAN AUDIT KESELAMATAN JALAN	DIREKABENTUK: NAMA	DILUKIS: NAMA	TARIKH:		
				JURUAUDIT KESELAMATAN JALAN	DISEMAK: NAMA	DILULUSKAN: NAMA	BIL. LUKISAN: KPKR/J/R/ _____		
							BIL. HELAIAN		

TITLE BLOCK FORMAT CONSULTANT DESIGN

- 1) Bilangan lukisan perlu didapati daripada pihak HOPT Cawangan Jalan.
- 2) Susunatur lukisan perlu merujuk kepada Standard Drawings For Road Construction dan contoh List of Drawings yang disertakan.

NOTA :
Hendaklah ditandatangani oleh Pengarah Syarikat Perunding yang bertauliah dalam bidang berkaitan.

NOTA:
NAMA CAWANGAN (HODT) YANG BERKAITAN DENGAN SKOP KERJA BERIKUT:

1. CAWANGAN JALAN
2. CAWANGAN KEJURUTERAAN GEOTEKNIK
3. CAWANGAN KEJURUTERAAN ELEKTRIK
4. CAWANGAN ALAM SEKITAR & TENAGA


P.E STAMP & SIGNATURE

I PROFESSIONAL ENGINEER (REG. NO.) HEREBY CONFIRM THAT THE DESIGNS SHOWN IN THIS CALCULATIONS/DRAWINGS/SPECIFICATIONS WAS DESIGNED BY ME OR UNDER MY DIRECTION AND SUPERVISION AND TO THE BEST OF MY KNOWLEDGE, COMPLY WITH THE RELEVANT ENGINEERING STANDARDS AND CODES OF PRACTICE, AND LOCAL AUTHORITIES BY LAW AND REGULATIONS.

TARIKH	BUTIRAN	RUJUKAN	JURUKUR NAMA & ALAMAT	PERUNDING NAMA & ALAMAT			NAMA CAWANGAN	CAWANGAN JALAN	 JABATAN KERJA RAYA MALAYSIA	 KEMENTERIAN KERJA RAYA MALAYSIA		
							NAMA PENGARAH	NAMA PENGARAH KANAN				
PINDAAN				UKURAN	DIREKABENTUK: NAMA	DILUKIS: NAMA	JURUAUDIT NAMA JURUAUDIT KESELAMATAN JALAN	NAMA KETUA PENOLONG PENGARAH KANAN (HODT)	NAMA KETUA PENOLONG PENGARAH KANAN (HOPT)	TAJUK PROJEK : TAJUK LUKISAN :	TARIKH:	BIL. LUKISAN: KPKR/J/R/ _____

KERAJAAN MALAYSIA

} Nama Jabatan



} Logo Jabatan

PEMBAIKAN DAN PENEMPATAN SEMULA
JALAN MELAKA - KENDONG
KILOMETER 7.25 KE KILOMETER 9.50
MELAKA


} Tajuk Projek

JILID III

} Jilid / Seksyen


OGOS 2012

} Tarikh Tender Projek



KETUA PENGARAH KERJA RAYA
IBU PEJABAT JABATAN KERJA RAYA MALAYSIA
JALAN SULTAN SALHUDDIN
50582 KUALA LUMPUR

} Alamat Ketua Pengarah Kerja Raya



LOGO, NAMA, ALAMAT & NO. TELEFON PERUNDING
ATAU
NAMA & ALAMAT LEAD HODT (IN-HOUSE DESIGN)

DRAWING NO. KPKR/J/R/ 1 2 3 4 5 6 / 7 8 / 9 10 11

TITLE

SHEET NO.

DRAWING NO. KPKR/J/R/ 1 2 3 4 5 6 / 7 8 / 9 10 11

TITLE

SHEET NO.

GENERAL

AM	1	COVER PAGE	1
AM	2	DRAWING INDEX	2
AM	3	LOCATION AND KEY PLAN	3
AM	4	ABBREVIATION SYMBOL AND LEGEND	4
AM	5	ELEMENTS OF CURVE	5
AM	6	SUPERELEVATION DETAILS	6
AM	7	TYPICAL ROAD CROSS SECTION	7
AM	8	PAVEMENT DETAILS	8
AM	9	SITE OFFICE	9

ALIGNMENT CONTROL PLAN AND LONGITUDINAL PROFILE

KB	1	ALIGNMENT CONTROL PLAN FROM CH. 0.000m TO CH. 1005.84m	10
KB	2	ALIGNMENT CONTROL PLAN FROM CH. 1005.84m TO CH. 7483.39m	11
KB	3	PLAN AND LONGITUDINAL SECTION FROM CH. 0.00m TO CH. 600.00m	12
KB	4	PLAN AND LONGITUDINAL SECTION FROM CH. 600.00m TO CH. 1200.00m	13
KB	5	PLAN AND PROFILE FROM CH. 0.00m TO CH. 600.00m	14
KB	6	PLAN AND PROFILE FROM CH. 600.00m TO CH. 1200.00m	15

CROSS SECTION

KL	1	CROSS SECTION FROM CH. 0.00m TO CH. 500.00m	16
KL	2	CROSS SECTION FROM CH. 500.00m TO CH. 1200.00m	17

JUNCTION LAYOUT

LP	1	JUNCTION DETAILS - GENERAL LAYOUT	18
LP	2	JUNCTION DETAILS - SETTING OUT	19
LP	3	JUNCTION DETAILS - PAVEMENT	20
LP	4	JUNCTION DETAILS - SUPERELEVATION	21

TRAFFIC CONTROL

KT	1	ROAD MARKING, TRAFFIC SIGNS & PROPOSED TRAFFIC SIGNAL	22
KT	2	SIGN POST DETAILS	23
KT	3	TRAFFIC MANAGEMENT PLAN (STAGE 1)	24
KT	4	TRAFFIC MANAGEMENT PLAN (STAGE 2)	25
KT	5	TRAFFIC MANAGEMENT PLAN (STAGE 3)	26

DRAINAGE

PP	1	TYPICAL DRAINAGE DETAILS	27
PP	2	DRAINAGE CHANNEL DETAILS	28
PP	3	INLET PITS DETAILS	29
PP	4	DETAILS OF BLOCK DRAIN AND CULVERT	30
PP	5	HEADWALL AND CONCRETE PIPE DETAILS (1)	31
PP	6	CULVERT SCHEDULE AND BEDDING DETAILS	32
PP	7	DRAINAGE PLAN FROM CH. 0.00m TO CH. 600.00m	33
PP	8	DRAINAGE PLAN FROM CH. 600.000m TO CH. 1200.000m	34

STRUCTURE

ST	1/1	BRIDGE NO. 1.0	- GENERAL ARRANGEMENT	35
ST	1/2		- BORED PILE	36
ST	1/3		- BEARING AND DOWEL BAR DETAILS	37
ST	2/1	BRIDGE NO. 2.0	- GENERAL ARRANGEMENT LAYOUT	38
ST	2/2		- BORED PILE	39
ST	2/3		- BEARING AND DOWEL BAR DETAILS	40

PUBLIC UTILITIES

PU	1	PROTECTION OF SERVICES PLAN	41
PU	2	RELOCATION OF SERVICES PLAN	42

ELECTRICAL

PE	1	STRIP MAP	43
PE	2	BLOCK DIAGRAM FOR ELECTRICAL DISTRIBUTION SYSTEM	44
PE	3	ROAD LIGHTING LAYOUT	45
PE	4	SCHEMATIC DIAGRAM FOR FEEDER PILLAR	46
PE	5	ROAD LIGHTING COLUMN DETAIL	47
PE	6	DETAIL OF CORBEL AND PIT	48
PE	7	TRAFFIC SIGNAL LIGHT LAYOUT	49
PE	8	SCHEMATIC DIAGRAM FOR TRAFFIC CONTROLLER	50

ENVIRONMENTAL PROTECTION WORKS





AS	1	ENVIRONMENTAL PROTECTION WORK PLAN FROM CH. 0.00m TO CH. 600.00m	51
AS	2	ENVIRONMENTAL PROTECTION WORK PLAN FROM CH. 600.00m TO CH. 1200.00m	52

GEOTECHNICAL

PG	1	GROUND TREATMENT SCHEDULE	53
PG	2	LOCATION OF SOIL PROFILE ON PLAN AND LONGITUDINAL PROFILE	54
PG	3	TYPICAL DETAILS OF GROUND TREATMENT	55

* TO REFER STANDARD DRAWING

TARIKH	BUTIRAN	RUJUKAN	UKURAN	JURUUKUR	CAWANGAN JALAN			 JABATAN KERJA RAYA MALAYSIA	PELANGGAN  KEMENTERIAN KERJA RAYA
					PENGARAH KANAN				
					PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN				
					JURUAUDIT	KETUA PENOLONG PENGARAH KANAN			
			JURUAUDIT KESELAMATAN JALAN	DIREKABENTUK:	DISEMAK:				
				DILUKIS:	DILULUSKAN:				
PINDAAN							TARIKH :	BIL. LUKISAN :	




PETUNJUK

- LEBUHRAYA TOL
- JALANRAYA TOL
- JALAN PERSEKUTUAN UTAMA
- LAIN-LAIN JALAN PERSEKUTUAN
- SEMPADAN ANTARABANGSA
- SEMPADAN NEGERI
- IBU NEGARA
- IBU NEGERI
- BANDAR PENTING
- BANDAR KECIL
- NOMBOR LALUAN
- PELABUHAN
- LAPANGAN TERBANG
- TANDA TINGGI UKURAN METER


(SUMBER : PETA JALAN PERSEKUTUAN, SEMENANJUNG MALAYSIA, PENERBITAN J.K.R.)

TARIKH	BUTIRAN		RUJUKAN	N.T.S UKURAN	JURUUKUR	CAWANGAN JALAN					 JABATAN KERJA RAYA MALAYSIA	 PELANGGAN KEMENTERIAN KERJA RAYA
						PENGARAH KANAN						
						PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN			KETUA PENOLONG PENGARAH KANAN (HOPT)			
						JURUAUDIT	KETUA PENOLONG PENGARAH KANAN (HOPT)					
						JURUAUDIT KESELAMATAN JALAN	DIREKABENTUK:	DISEMAK:				
					DILUKIS:	DILULUSKAN:		KEY PLAN & LOCATION PLAN		TARIKH:	Bil LUKISAN:	
PINDAAN												


MODEL DRAWING 4B




TARIKH	BUTIRAN	RUJUKAN	N.T.S UKURAN	JURUUKUR	CAWANGAN JALAN						JABATAN KERJA RAYA MALAYSIA		PELANGGAN	
					PENGARAH KANAN									
					PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN				KETUA PENOLONG PENGARAH KANAN (HOPT)					
					JURUAUDIT UNIT KESELAMATAN JALAN JURUAUDIT KESELAMATAN JALAN No Laporan Audit: CKJG/UKJ/000000000		KETUA PENOLONG PENGARAH KANAN (HODT)							
					DIREKABENTUK:		DISEMAK:							
PINDAAN			DILUKIS:		DILULUSKAN:		DETAIL LOCATION PLAN		TARIKH:	BIL. LUKISAN:				



TYPICAL EARTHWORKS SECTION



TYPICAL ROAD CROSS-SECTION FOR DUAL CARRIAGEWAY



TYPICAL ROAD CROSS-SECTION FOR SINGLE CARRIAGEWAY


NOTES

1. ALL DRAIN TYPES AND LOCATIONS SHALL BE AS SHOWN ON THE PLAN AND LONGITUDINAL SECTION DRAWINGS OR AS DIRECTED BY THE S.O.
2. ALL UNITS ARE IN mm UNLESS SHOWN OTHERWISE.
3. CONCRETE SHALL BE GRADE 20/20 EXCEPT FOR CONCRETE BUNDING.
4. DETAILS OF CROSS-SECTION DIMENSION SHOULD FOLLOW ATJ 8/86
5. CUT SLOPE INCLINATION ANGLE SHOULD BE DESIGNED.
6. FILL EMBANKMENT DESIGN IS 1 : 2
7. IF THE GRADIENT OF THE FILL EMBANKMENT IS STEEPER, SLOPE INCLINATION ANGLE SHOULD BE DESIGNED.
8. ALL DETAILS OF THICKNESS OF PAVEMENT STRUCTURE SHALL BE DESIGNED ACCORDING TO ATJ 5/85 (PINDAMAN 2013)

TABLE 1 : CROSS-SECTIONAL DIMENSIONS

STANDARD	R5	R4	R3	R2	R1	U5	U4	U3	U2	U1
ITEM										
C (m)	7.00	7.00	7.00	7.00	5.00	7.00	6.5	6.00	5.50	5.00
C1 (m)	3.5	3.25	3.00	2.75	2.50	3.50	3.25	3.00	2.75	2.50
L (m)	3.00	3.00	2.50	2.00	1.50	3.00	3.00	2.50	2.00	1.50
L1 (m)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
S (%)	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5
S1 (%)	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00	4.00
%max (ratio)	0.10	0.10	0.10	0.10	0.10	0.06	0.06	0.06	0.06	0.06
Ms (m)	0.50	0.25	0.25	0.00	0.00	0.50	0.25	0.25	0.00	0.00


ROAD DESIGN TO STANDARD




DETAIL 'A'
TYPICAL PAVEMENT SECTION FOR MAIN ROAD

TABLE 2

WEARING COURSE (mm)	
BINDER COURSE (mm)	
CRUSHED AGGREGATE ROAD BASE (mm)	
SUBBASE (mm)	
DESIGN PERIOD (year)	
CUMULATIVE TOTAL EQUIVALENT STANDARD AXLE (BASE YEAR)	
DESIGN SUBGRADE CBR (%)	
ROAD DESIGN STANDARD	




DETAIL 'B'
TYPICAL DETAILS OF PREMIX SIDEWALK



DETAIL 'B'
TYPICAL DETAILS OF CONCRETE SLAB SIDEWALK

TARIKH	BUTIRAN	RUJUKAN	N.T.S UKURAN	JURUUKUR	CAWANGAN JALAN					JABATAN KERJA RAYA MALAYSIA		PELANGGAN  KEMENTERIAN KERJA RAYA
LUKSAN INI TELAH DILUKIS SEMULA DARIPADA KPKR/JJ/R/STD/AM 116 STANDARD DRAWINGS FOR ROAD CONSTRUCTION 1989					PENGARAH KANAN					KETUA PENOLONG PENGARAH KANAN (HOP T)		
					PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN							
					JURUAUDIT	KETUA PENOLONG PENGARAH KANAN (HOD T)						
		JURUAUDIT KESELAMATAN JALAN			DIREKABENTUK:	DISEMAK:			TARIKH:	BIL.		
			DILUKIS:	DILULUSKAN:				LUKISAN:				
PINDAAN									TYPICAL ROAD CROSS - SECTION			

NAMA PROJEK : ()



LEGEND:

A - Mill ____mm. Replace ____mm

B - Mill ____mm. Replace ____mm

C - Mill ____mm Replace ____mm

D - Reconstruction (Refer Drawing No _____)

E - Overlay ____mm

F - Crack Sealing

G - Cold in Place Recycling (CIPR)

H - Hot in Place Recycling (HIPR)

Mill and replace

Reconstruction


HIPR

CIPR


Crack sealing

Overlay


TARIKH	BUTIRAN	RUJUKAN	JURUUKUR	CAWANGAN JALAN				JABATAN KERJA RAYA MALAYSIA	PELANGGAN
				PENGARAH KANAN					
				PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN		KETUA PENOLONG PENGARAH KANAN (HOPT)			
			N.T.S UKURAN	JURUAUDIT	KETUA PENOLONG PENGARAH KANAN (HODT)		KETUA PENOLONG PENGARAH KANAN (HOPT)	PAVEMENT REHABILITATION DETAIL	
				JURUAUDIT KESELAMATAN JALAN	DIREKABENTUK:	DISEMAK:			
				DILUKIS:	DILULUSKAN:		TARIKH:	BIL. LUKISAN:	




TYPICAL CROSS SECTION FOR CONCRETE ROAD



TYPICAL ROAD PLAN



CONSTRUCTION JOINT




DETAIL 'A'

ROAD TYPE	mm		
	W	S	J
A	3000	1500	5000
B	4000	1500	5000
C	5000	2000	6000

TABLE 1

W = CARRIAGEWAY WIDTH
S = SHOULDER WIDTH
J = CONTRACTION JOINT SPACING

FOR THIS PROJEK USE ROAD TYPE _____



PAVEMENT DETAILS

SPECIFICATIONS

1. THE TYPE OF ROAD SHALL BE DETERMINED BY THE DESIGNER. (TABLE 1)
2. THE CONCRETE SHALL BE GRADE _____ WITH A WATER CEMENT RATIO NOT EXCEEDING 0.50.
3. CEMENT SHALL BE ORDINARY PORTLAND CEMENT CONFORMING TO M.S. 522.
4. COARSE AGGREGATES SHALL CONFORM TO M.S. 29. MAXIMUM SIZE NOT EXCEED 40.00 mm.
5. SAND SHALL CONFORM WITH M.S. 30.
6. ADMIXTURE, IF USED, SHALL BE APPROVED BY THE S.O. AND SHALL CONFORM TO M.S. 922.
7. WATER SHALL CONFORM TO M.S. 28.
8. STEEL SHALL CONFORM TO M.S. 146.
9. SEALANT FOR JOINT SHALL BE HOT - POURED TYPE CONFORMING TO B.S. 2499 FOR TYPE A2 SEALANTS.
10. WATERPROOF MEMBRANE SHALL BE PLASTIC SHEETING 125 mm THICK.
11. DOWEL BARS SHALL BE DEBONDED WITH A COATING MC - 2 BITUMEN.
12. CURING SHALL BE BY APPLICATION OF AN APPROVED LIQUID MEMBRANE - FORMING COMPOUND COMPLYING WITH A KASHTO. M148 TYPE 2 (WHITE PIGMENTED) AT A RATE OF 0.22 - 0.27 LITRE / m² BY MECHANICAL SPRAYER.
13. SHOULDER MATERIAL SHALL BE NATURALLY OCCURRING EARTH AGGREGATE CONFORMING TO THE FOLLOWING GRADING.

B.S. SIEVE SIZE (mm)	% BY WEIGHT PASSING
20.00	100
10.00	75 - 100
5.00	50 - 75
2.00	30 - 60
0.425	15 - 35
0.075	5 - 15


THE PORTION PASSING THE 0.425 mm. IF IT IS PLASTIC SHALL HAVE :

- a) LIQUID LIMIT 40%
- b) WITHIN 5% - 15% PLASTIC INDEX PLASTICITY

14. SUBBASE SHALL BE RIVER OR TIN MINING SAND CONFORMING TO THE FOLLOWING GRADING.



B.S. SIEVE SIZE (mm)	% BY WEIGHT PASSING
10.00	100
2.00	65 - 100
1.18	45 - 80
0.300	10 - 30
0.150	2 - 10

15. CONCRETE SURFACE SHALL BE BROOM FINISHED AS DIRECTED BY THE S.O.
16. MINIMUM OVERLAP OF PLASTIC SETTING SHALL BE 300 mm.

















TRANSVERSE CONTRACTION JOINT DETAILS

TARIKH	BUTIRAN	RUJUKAN	JURUUKUR	CAWANGAN JALAN		JABATAN KERJA RAYA MALAYSIA	PELANGGAN
				PENGARAH KANAN			
				PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN			
				JURUAUDIT	KETUA PENOLONG PENGARAH KANAN (HOPT)		
				JURUAUDIT KESELAMATAN JALAN	DIREKABENTUK:	DISEMAK:	
					DILUKIS:	DILULUSKAN:	
PINDAAN						TARIKH:	BIL. LUKISAN:




TARIKH	BUTIRAN	RUJUKAN	JURUUKUR	CAWANGAN JALAN		JKR	JABATAN KERJA RAYA MALAYSIA		PELANGGAN
				PENGARAH KANAN					
				PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN					
				JURUAUDIT	KETUA PENOLONG PENGARAH KANAN (HODT)				
				JURUAUDIT KESELAMATAN JALAN	DIREKABENTUK:	DISEMAK:			
					DILUKIS:	DILULUSKAN:			
PINDAAN									
						ALIGNMENT CONTROL PLAN			
						TARIKH:		BIL. LUKISAN:	

[illegible]





TARIKH	BUTIRAN	RUJUKAN	JURUUKUR	CAWANGAN JALAN			JABATAN KERJA RAYA MALAYSIA		PELANGGAN
				PENGARAH KANAN					
				PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN					
				JURUAUDIT	KETUA PENOLONG PENGARAH KANAN (HOPT)				
				JURUAUDIT KESELAMATAN JALAN	DIREKABENTUK:	DISEMAK:			
					DILUKIS:	DILULUSKAN:			
PINDAAN			N.T.S UKURAN				CROSS SECTION		
							TARIKH:	BIL. LUKISAN:	






TARIKH	BUTIRAN		RUJUKAN	1 : 50 UKURAN	JURUUKUR	CAWANGAN JALAN				 JABATAN KERJA RAYA MALAYSIA	 PELANGGAN KEMENTERIAN KERJA RAYA	
						PENGARAH KANAN						
						PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN						
						JURUAUDIT	KETUA PENOLONG PENGARAH KANAN		KETUA PENOLONG PENGARAH KANAN (HOPT)			
PINDAAN				JURUAUDIT KESELAMATAN JALAN		DIREKABENTUK:	DISEMAK:					
						DILUKIS:	DILULUSKAN:					
						JUNCTION DETAILS - PAVEMENT SUPERELEVATION				TARIKH :	BIL. LUKISAN :	





0	11	15	17	28	33	34	46	50	52	64	88	SECOND
GREEN	A	RED										
RED	GREEN	A	RED									
RED					GREEN	A	R					
RED										GREEN	A	R




LEGEND:
→ PRIMARY
→ SECONDARY
• MAST ARM

- LEGEND
- TYPE 1 CONTINUITY LINE
 - TYPE 2 GIVE-WAY LINE
 - TYPE 4 CENTER LINE/LANE LINE
 - TYPE 6 EDGE LINE/CHANNELISING LINE
 - TYPE 7 STOP LINE WITH PEDESTRIAN
 - TYPE 10 DOUBLE LINE


TARIKH	BUTIRAN	RUJUKAN	JURUUKUR	CAWANGAN JALAN				JABATAN KERJA RAYA MALAYSIA	PELANGGAN
				PENGARAH KANAN					
				PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN					
				JURUAUDIT	KETUA PENOLONG PENGARAH KANAN (HOPT)		KETUA PENOLONG PENGARAH KANAN (HOPT)	ROAD MARKING, TRAFFIC SIGNS & TRAFFIC SIGNAL	KEMENTERIAN KERJA RAYA
				JURUAUDIT KESELAMATAN JALAN	DIREKABENTUK:	DISEMAK:			
					DILUKIS:	DILULUSKAN:			
PINDAAN				N.T.S	TARIKH:				BIL LUKISAN:




TARIKH	BUTIRAN	RUJUKAN	1 : 1 1 : 2 UKURAN	JURUUKUR	CAWANGAN JALAN			 JABATAN KERJA RAYA MALAYSIA  PELANGGAN KEMENTERIAN KERJA RAYA	DRAINAGE PLAN		
					PENGARAH KANAN						
					PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN						
					JURUAUDIT JURUAUDIT KESELAMATAN JALAN	KETUA PENOLONG PENGARAH KANAN DIREKABENTUK: DILUKIS:	DISEMAK: DILULUSKAN:				KETUA PENOLONG PENGARAH KANAN (HOPT)
PINDAAN								TARIKH :	BIL. LUKISAN :		




SIGN 1





SIGN 2




SECTION B-B




SECTION C-C




SECTION A-A



SECTION D-D




TRAFFIC BARRIER DETAIL



- GENERAL NOTES :**
- Contractor shall ensure that the traffic along the existing road is to be maintained through out the full duration of the contract.
 - Construction should be carried out in stages.
 - The no. of stages shown in the plans are meant for guidance only. The actual no. of stages, sequence of work and duration shall be determined by contractor. The contractor shall submit full details of his proposed traffic management diversion plans and method statement for approval of the S.O before commencing works.
 - All temporary diversion must be constructed in advance of the existing roadways and regularly maintained for as long as required in a satisfactory conditions.
 - Shuttle barrier (SB) constitutes the following:
 - Warning lamp at 10 meter interval
 - Reflective string
 - Water filled NJ Barriers must be interlocked at all time.
 - Shuttle barrier used during the initial stage will be relocated / re used where appropriate for the following stage.
 - Temporary traffic signs shall be of fluorescent orange prismatic retro-reflective sheeting.
 - The working area for construction shall be minimum of 200 meter length at one time and to be revised accordingly to S.O instruction. Flagmen shall be stationed fully at working area to ensure that vehicles are guided accordingly along the working area.
 - Traffic Management Plan also needs to be applied on the straight road.
 - Reduction of the speed limit at the construction site cannot be more than 20km/h from the existing speed.

TARIKH	BUTIRAN	RUJUKAN	1:1000 UKURAN	JURUUKUR	CAWANGAN JALAN						JABATAN KERJA RAYA MALAYSIA						PELANGGAN KEMENTERIAN KERJA RAYA
					PENGARAH KANAN						TRAFFIC MANAGEMENT PLAN - STAGE 1						
					PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN			KETUA PENOLONG PENGARAH KANAN (HOPT)									
					JURUAUDIT	KETUA PENOLONG PENGARAH KANAN (HODT)											
PINDAAN					JURUAUDIT KESELAMATAN JALAN	DIREKABENTUK:		DISEMAK:		TARIKH:							
						DILUKIS:		DILULUSKAN:									



- GENERAL NOTES :
- Contractor shall ensure that the traffic along the existing road is to be maintained through out the full duration of the contract.
 - Construction should be carried out in stages.
 - The no. of stages shown in the plans are meant for guidance only. The actual no. of stages, sequence of work and duration shall be determined by contractor. The contractor shall submit full details of his proposed traffic management diversion plans and method statement for approval of the S.O before commencing works.
 - All temporary diversion must be constructed in advance of the existing road ways and regularly maintained for as long as required in a satisfactory conditions.
 - Shuttle barrier (SB) constitute of the following:
 - Warning lamp at 10 meter interval
 - Reflective string
 - Water filled NJ Barriers must be interlocked at all time.
 - Shuttle barrier used during the initial stage will be relocated / re used where appropriate for the following stage.
 - Temporary traffic signs shall be of fluorescent orange prismatic retro-reflective sheeting.
 - The working area for construction shall be minimum of 200 meter length at one time and to be revise accordingly to S.O instruction. Flagmen shall be station fully at working area to ensure that vehicles are guided accordingly along the working area.
 - Traffic Management Plan also need to be applied on the straight road.
 - Reduction of the speed limit at the construction site can not more than 20km/h from the existing speed.

TARIKH	BUTIRAN	RUJUKAN	1:1000 UKURAN	JURUUKUR	CAWANGAN JALAN					JABATAN KERJA RAYA MALAYSIA			PELANGGAN
					PENGARAH KANAN					TRAFFIC MANAGEMENT PLAN - STAGE 2A			
					PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN			KETUA PENOLONG PENGARAH KANAN (HOPT)					
					JURUAUDIT	KETUA PENOLONG PENGARAH KANAN (HODT)							
					JURUAUDIT KESELAMATAN JALAN	DIREKABENTUK:	DISEMAK:						
						DILUKIS:	DILULUSKAN:						
PINDAAN									TARIKH:	BIL. LUKISAN:			




 WORKING ZONE
 CENTRE LINE OF NEW ROAD
 BARRIER/ BARRICADE SYMBOL

- 



TRAFFIC MANAGEMENT PLAN - STAGE 2B

BIL.	LUKISAN:
------	----------

TARIKH	BUTIRAN	RUJUKAN	1:1000 UKURAN	JURUUKUR	CAWANGAN JALAN					JABATAN KERJA RAYA MALAYSIA		PELANGGAN  KEMENTERIAN KERJA RAYA
					PENGARAH KANAN					KETUA PENOLONG PENGARAH KANAN (HOPT)		
					PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN							
					JURUAUDIT	KETUA PENOLONG PENGARAH KANAN (HOPT)						
PINDAAN					JURUAUDIT KESELAMATAN JALAN	DIREKABENTUK:	DISEMAK:			TARIKH:	BIL LUKISAN:	
				DILUKIS:	DILULKUSAN:							
TRAFFIC MANAGEMENT PLAN - STAGE 2B												





SECTION C-C




TARIKH	BUTIRAN	RUJUKAN	1:1000 UKURAN	JURUUKUR	CAWANGAN JALAN							JABATAN KERJA RAYA MALAYSIA				 PELANGGAN
					PENGARAH KANAN							TRAFFIC MANAGEMENT PLAN - STAGE 3				
					PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN				KETUA PENOLONG PENGARAH KANAN (HOPT)							
					JURUAUDIT	KETUA PENOLONG PENGARAH KANAN (HODT)										
					JURUAUDIT KESELAMATAN JALAN	DIREKABENTUK:	DISEMAK:									
							DILUKIS:	DILULUSKAN:		TARIKH:				BIL. LUKISAN:		

NOTES

1. LENGTH OF BRIDGE = 20.0+40.0+20.0m=80.0m
2. LOADING:BD 37/01
3. ALL DIMENSIONS ARE IN mm UNLESS STATED OTHERWISE.
4. LEGEND : SL = SOFT LEVEL HWL=HIGHEST WATER LEVEL
NWL = NORMAL WATER LEVEL RL = REDUCED LEVEL
FRL=FINISHED ROAD LEVEL
5. JKR FILE REFERENCES:PKR RPJ 06/31/001
- 6 THIS SET COMPRISES A TOTAL OF 12 DRAWINGS AS FOLLOW:
- DRAWING NO KPK /J/068501/0/ST(0)-GENERAL LAYOUT
- ST(2)-SOIL DATA
- ST(3)-#600mm CYLINDRICAL PILE
- ST(4)-ABUTMENT CONCRETE
- ST(5)-ABUTMENT CONCRETE
- ST(6)-#600mm CYLINDRICAL PILE
- ST(7)-PIER CONCRETE
- ST(8)-PIER REINFORCEMENT
- ST(9)-PRESTRESSED BEAM - CONCRETE
- ST(10)-PRESTRESSED BEAM - REINFORCEMENT
- ST(11) DECK SLAB AND DIAPHRAGM
- ST(12)-PARAPET AND HANDRAIL
- 
- GUARDRAIL



ELEVATION
SCALE 1: 200



TARIKH	BUTIRAN	RUJUKAN	1 : 50 UKURAN	JURUUKUR	CAWANGAN JALAN				 JABATAN KERJA RAYA MALAYSIA	 PELANGGAN KEMENTERIAN KERJA RAYA
					PENGARAH KANAN					
					PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN					
					JURUAUDIT	KETUA PENOLONG PENGARAH KANAN		KETUA PENOLONG PENGARAH KANAN (HOPT)		
					JURUAUDIT KESELAMATAN JALAN	DIREKABENTUK:	DISEMAK:			
				DILUKIS:	DILULUSKAN:					
PINDAAN								TARIKH :	BIL. LUKISAN :	





TABLE 1


STRUCTURE	NO OF PILES	ESTIMATED LENGTH OF PILE (m)	DIAMETER OF PILE (X) (m)	BONDED IN HARD LAYERS SPT > 50 (m)	SOCKETED IN ROCK (m)	DESIGN LOAD OF PILES (kN)
	VERTICAL					
ABUTMENT A						
ABUTMENT B						
PIER 1						
PIER 2						

NOTES:


- a) CONCRETE SHALL BE OF GRADE 35/20, WITH THE MAXIMUM WATER/CEMENT RATIO OF 0.5
b) THE SLUMP SHALL BE BETWEEN 125mm TO 175mm WITH APPROVED SUPER PLASTICIZER.
- NOMINAL CONCRETE COVER SHALL BE 75mm.
- THE CONTRACTOR SHALL PROVIDE A SUPERVISOR WITH PREVIOUS EXPERIENCES ON BORED PILING.
- DILLING OPERATION OF BORE SHAFT SHALL BE COMPLETED IN A SINGLE OPERATION AND CONCRETING SHALL BE CARRIED OUT IMMEDIATELY AFTER CLEANING THE HOLE AND CARRIED OUT CONTINUOUSLY UNTIL COMPLETION
- ALL REINFORCEMENT TO CONFORM TO MS 146 fy =400 N/mm2.
- TEMPORARY STEEL CASING SHALL BE ADOPTED FOR THE INSTALLATION OF BOREPILES IF THE FOLLOWING CONDITIONS ARE MET:-
a) TEST ON THE INITIAL BOREPILE INSTALL WITH TEMPORARY STEEL CASING SHOWS THAT THE PILE INTEGRITY IS NOT COMPROMISED. i.e. PILE NECKING, ETC.
b) THE OPERATION OF PULLING THE TEMPORARY STEEL CASING DOES NOT CAUSE ANY ADVERSE EFFECTS TO THE ENVIRONMENT IN TERM OF NOISE, VIBRATION, DAMAGE TO EXISTING STRUCTURES, EXCESSIVE SETTLEMENT OF GROUND ETC.
c) THE OPERATION OF PULLING THE TEMPORARY STEEL CASING SHALL BE COMPLETED BY 10.00 PM. WHICH IS THE LIMIT OF WORKING HOURS.
- IN THE EVENT THAT NONE OF THE ABOVE CONDITION IN NOTE 6 CAN BE MET ALL TEMPORARY STEEL CASING SHALL BE LEFT IN PLACE AS A PERMANENT STEEL CASING.
- TEST LOAD TO TWICE WORKING LOAD.
- ALL DIMENSIONS ARE IN mm UNLESS STATED OTHERWISE.
- MAXIMUM PERMISSABLE DEVIATION OF THE PILE CENTER SHALL NOT EXCEED 75mm



TARIKH	BUTIRAN	RUJUKAN	JURUUKUR	CAWANGAN JALAN				JABATAN KERJA RAYA MALAYSIA		
				PENGARAH KANAN						
				PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN						
				JURUAUDIT	KETUA PENOLONG PENGARAH KANAN					
				JURUAUDIT KESELAMATAN JALAN	DIREKABENTUK:	DISEMAK:	KETUA PENOLONG PENGARAH KANAN (HOPT)			
					DILUKIS:	DILULUSKAN:				
PINDAAN								TARIKH :	BIL. LUKISAN :	

[illegible]


TARIKH	BUTIRAN	RUJUKAN	1:50 UKURAN	JURUUKUR	CAWANGAN JALAN			 JABATAN KERJA RAYA MALAYSIA	PELANGGAN  KEMENTERIAN KERJA RAYA
					PENGARAH KANAN				
					PENGARAH PAKAR KEJURUTERAAN JALAN & JAMBATAN				
					JURUAUDIT JURUAUDIT KESELAMATAN JALAN	KETUA PENOLONG PENGARAH KANAN DIREKABENTUK: DISEMAK: DILUKIS: DILULUSKAN:	KETUA PENOLONG PENGARAH KANAN (HOPT)		
PINDAAN					BEARING AND DOWEL BAR DETAILS			TARIKH : BIL. LUKISAN :	



KERAJAAN MALAYSIA
JABATAN KERJA RAYA MALAYSIA

**PEMASANGAN SISTEM ELEKTRIK UNTUK
[TAJUK PROJEK]**

[TARIKH]



PEJABAT PENGARAH KANAN
CAWANGAN KEJURUTERAAN ELEKTRIK
IBU PEJABAT JKR MALAYSIA
TINGKAT 11, BLOK G,
NO. 6, JLN SULTAN SALAHUDDIN,
50480 KUALA LUMPUR
MALAYSIA

BAHAGIAN PERUNDING REKABENTUK (KUMPULAN E)
CAWANGAN KEJURUTERAAN ELEKTRIK
IBU PEJABAT JKR MALAYSIA

[TAJUK PROJEK]

LIST OF DRAWINGS :


BIL	DRAWING NO. (Refer Drawing Index)	DESCRIPTION
1	KPKR/J/R/_	LIST OF DRAWINGS
2	KPKR/J/R/_	STRIP MAP AND DESIGN CRITERIA
3	KPKR/J/R/_	BLOCK DIAGRAM FOR ELECTRICAL SUPPLY SYSTEM
4	KPKR/J/R/_	ROAD LIGHTING LAYOUT AT JUNCTION (NO. __)
5	KPKR/J/R/_	ROAD LIGHTING LAYOUT AT BRIDGE
6	KPKR/J/R/_	SCHEMATIC DIAGRAM FOR FEEDER PILLAR 1A AT JUNCTION (NO. __)
7	KPKR/J/R/_	ROAD CROSS SECTION OF ROAD LIGHTING
8	KPKR/J/R/_	ROAD LIGHTING COLUMN & TECHNICAL INFORMATION
9	KPKR/J/R/_	ROAD LIGHTING COLUMN DETAIL 1
10	KPKR/J/R/_	ROAD LIGHTING COLUMN DETAIL 2
11	KPKR/J/R/_	CORBEL AND PIT DETAIL @ PARAPET (BRIDGE)

LIST OF DRAWINGS :

BIL	DRAWING NO. (Refer Drawing Index)	DESCRIPTION
12	KPKR/J/R/_	TRAFFIC SIGNAL LIGHT LAYOUT AT JUNCTION (NO. __)
13	KPKR/J/R/_	SCHEMATIC DIAGRAM FOR TRAFFIC SIGNAL LIGHT CONTROLLER AT JUNCTION (NO. __)

TARIKH	BUTIRAN	RUJUKAN	JURUAUDIT	CAWANGAN KEJURUTERAAN ELEKTRIK		CAWANGAN JALAN	 JABATAN KERJA RAYA MALAYSIA			NAMA PELANGGAN
			NO. LAPORAN AUDIT :	PENGARAH KANAN	PENGARAH PERUNDING REKABENTUK	PENGARAH KANAN	PROJEK:			
				KETUA JURUTERA ELEKTRIK	JURUTERA ELEKTRIK PENGUASA					
				JURUTERA ELEKTRIK	PENOLONG JURUTERA ELEKTRIK					
PINDAAN						KETUA PENOLONG PENGARAH KANAN (HOPT)	TARIKH:	SKALA: N.T.S	BIL. LUKISAN:	BIL. HELAIAN:

STRIP MAP FOR ELECTRICAL WORK SCOPE



TARIKH	BUTIRAN	RUJUKAN	JURUAUDIT	CAWANGAN KEJURUTERAAN ELEKTRIK		CAWANGAN JALAN	JABATAN KERJA RAYA MALAYSIA		NAMA PELANGGAN	
			NO. LAPORAN AUDIT :	PENGARAH KANAN	PENGARAH PERUNDING REKABENTUK	PENGARAH KANAN	 JABATAN KERJA RAYA MALAYSIA			
				KETUA JURUTERA ELEKTRIK	JURUTERA ELEKTRIK PENGUASA		PROJEK:			
				JURUTERA ELEKTRIK	PENOLONG JURUTERA ELEKTRIK		BUTIRAN: STRIP MAP FOR ELECTRICAL WORK SCOPE			
PINDAAN						KETUA PENOLONG PENGARAH KANAN (HOPT)	TARIKH:	SKALA: N.T.S.	BIL. LUKISAN:	BIL. HELAIAN:

DESIGN CRITERIA OF ROAD LIGHTING

DESIGN STANDARDS

- THE FOLLOWING DESIGN STANDARDS ARE USED IN DESIGNING ROAD LIGHTING.
- MS 825 : PART 1, 2007 - CODE OF PRACTICE FOR THE DESIGN OF ROAD LIGHTING LIGHTING OF ROADS AND PUBLIC AMENITY AREAS
 - CIE 115-1995 : RECOMMENDATIONS FOR THE LIGHTING OF ROADS FOR MOTOR AND PEDESTRIAN TRAFFIC
 - IEC 60598-2-3 : LUMINAIRES
 - L-S20 : SPECIFICATION FOR ROAD LIGHTING INSTALLATION

DESIGN CRITERIA

ITEM	TYPICAL CONFLICT AREA (JUNCTION)
LIGHTING CLASS	CE2
MINIMUM MAINTAINED AVERAGE ILLUMINANCE (LUX)	20 LUX
ILLUMINANCE (INITIAL) / REQUIRED	24 LUX
OVERALL UNIFORMITY (E Min/ E Ave)	≥0.4
LONGITUDINAL UNIFORMITY (Emin / Emax)	-
DISABILITY GLARE (TI)	-
MAINTENANCE FACTOR	0.83 (ASSUMPTION : CLEANING INTERVAL = 36 MONTH, MEDIUM POLLUTION, IP 6X MIN)
LIGHTING ARRANGEMENT	STAGGERED & OPPOSITE
AVERAGE DISTANCE	AT GRADE 40m AT BRIDGE (PARAPET) 35m
ROAD SURFACE TYPE	ASPHALT, Q _o = 0.07
CLASS OF ROAD = R3	

TYPE OF LUMINAIRES AND COLUMNS

TYPE OF COLUMNS :-

- > ALL COLUMNS USED ARE OCTAGONAL HOT-DIPPED GALVANISED IRON (2 SECTIONS)
- > LIGHTING COLUMNS ARE DESIGNED TO WITHSTAND A WIND SPEED OF 35m/s²

TYPE OF LUMINAIRES :-


- > TYPE OF LUMINAIRES USED WILL BE AS FOLLOWS :

AREA	TYPE OF FITTING	LAMP LUMEN	ARM LENGTH	TILTING ANGLE
JUNCTION	1 X 250W HPSV LUMINAIRE MOUNTED ON 10m POLE	28000 Lm	2.5 m (WITH ARM)	5°
BRIDGE	1 X 250W HPSV LUMINAIRE MOUNTED ON 9m POLE AT BRIDGE PARAPET	28000 Lm	2.5 m (WITH ARM)	5°

- > ALL LIGHT LUMINAIRES WILL MEET THE MINIMUM REQUIREMENT OF IP66 FOR OPTICAL COMPARTMENT AND MINIMUM IP43 FOR CONTROL GEAR COMPARTMENT.
- > ACCESS TO THE INTERIOR OF THE LUMINAIRE SHALL BE FROM THE TOP. BOTTOM ACCESS IS NOT ACCEPTABLE.
- > MAIN SUPPORTING STRUCTURE OF LUMINAIRE MADE OF DIE-CAST ALUMINIUM ALLOY MATERIALS.. GRP / FRP MATERIAL IS NOT ACCEPTABLE.


TARIKH	BUTIRAN	RUJUKAN	JURUAUDIT	CAWANGAN KEJURUTERAAN ELEKTRIK		CAWANGAN JALAN	JABATAN KERJA RAYA MALAYSIA		NAMA PELANGGAN
				PENGARAH KANAN	PENGARAH PERUNDING REKABENTUK				
				KETUA JURUTERA ELEKTRIK	JURUTERA ELEKTRIK PENGUASA				
				JURUTERA ELEKTRIK	PENOLONG JURUTERA ELEKTRIK				
PINDAAN				NO. LAPORAN AUDIT :		KETUA PENOLONG PENGARAH KANAN (HOPT)	BUTIRAN: DESIGN CRITERIA		KEMENTERIAN KERJA RAYA
						TARIKH:	SKALA: N.T.S	BIL. LUKISAN:	BIL. HELAIAN:

BLOCK DIAGRAM FOR ELECTRICAL SUPPLY SYSTEM



SURAT KELULUSAN
TNB/SESCO/SESB
RUJUKAN : XXXXXXXX
TARIKH : YY-YY-YYYY

TARIKH	BUTIRAN	RUJUKAN	JURUAUDIT	CAWANGAN KEJURUTERAAN ELEKTRIK		CAWANGAN JALAN	JABATAN KERJA RAYA MALAYSIA		NAMA PELANGGAN
				PENGARAH KANAN	PENGARAH PERUNDING REKABENTUK		PROJEK:		
				KETUA JURUTERA ELEKTRIK	JURUTERA ELEKTRIK PENGUASA		BUTIRAN:	BLOCK DIAGRAM FOR ELECTRICAL DISTRIBUTION SYSTEM	KEMENTERIAN KERJA RAYA
				JURUTERA ELEKTRIK	PENOLONG JURUTERA ELEKTRIK		TARIKH:	SKALA:	BIL. LUKISAN:
								N.T.S	
	PINDAAN		NO. LAPORAN AUDIT :			KETUA PENOLONG PENGARAH KANAN (HOPT)			BIL. HELAIAN:



LEGEND

SYMBOL	DESCRIPTION	QTY
	1 X 250W HPSV LUMINAIRE MOUNTED ON 12m COLUMN WITH ARM LENGTH 2.5m (FLANGED TYPE)	22
	2 X 250W HPSV LUMINAIRE MOUNTED ON 12m COLUMN WITH ARM LENGTH 2.5m (FLANGED TYPE)	12
	FEEDER PILLAR	2
	4C 16mm PVC/SWA/PVC UNDERGROUND ALUMINIUM CABLE LAID IN DOUBLE LAYER CORRUGATED HDPE PIPE	410m
	4C 16mm PVC/SWA/PVC UNDERGROUND ALUMINIUM CABLE DIRECT BURRIED	1100m
	150mm dia. G.I. PIPE CLASS C	160m
Notes: AVERAGE DISTANCE BETWEEN ROAD LIGHTING (MAIN LINE) = 40m		


TARIKH	BUTIRAN	RUJUKAN	JURUAUDIT	CAWANGAN KEJURUTERAAN ELEKTRIK		CAWANGAN JALAN	JABATAN KERJA RAYA MALAYSIA		NAMA PELANGGAN
			UNIT KESELAMATAN JALAN	PENGARAH KANAN	PENGARAH PERUNDING REKABENTUK		PROJEK:		
				KETUA JURUTERA ELEKTRIK	JURUTERA ELEKTRIK PENGUASA				
				JURUTERA ELEKTRIK	PENOLONG JURUTERA ELEKTRIK		BUTIRAN: ROAD LIGHTING LAYOUT AT JUNCTION (No.)		KEMENTERIAN KERJA RAYA
	PINDAAN		NO. LAPORAN AUDIT :			KETUA PENOLONG PENGARAH KANAN (HOPT)	TARIKH:	SKALA: 1: 1500	BIL. LUKISAN:

Model Drawing No. 15G

LEGEND

SYMBOL	DESCRIPTION	QTY
	1 X 250W HPSV LUMINAIRE MOUNTED ON 12m COLUMN WITH ARM LENGTH 2.5m - AT GRADE (FLANGED TYPE)	12
	1 X 250W HPSV LUMINAIRE MOUNTED ON 11m COLUMN WITH ARM LENGTH 2.5m - AT BRIDGE (FLANGED TYPE)	4
	FEEDER PILLAR	1
	400mm X 400mm X 500mm CABLE PIT C/W COVER	4
	4C 16mm PVC/SWA/PVC ALUMINIUM CABLE	820m
	150mm dia. G.I. PIPE CLASS C	25m


Notes:
 AVERAGE DISTANCE BETWEEN ROAD LIGHTING COLUMN = 40 m (OPPOSITE ACROSS) AT GRADE
 AVERAGE DISTANCE BETWEEN ROAD LIGHTING AT BRIDGE = 35 m (STAGGERED) AT BRIDGE




SKALA: 1 : 1500

TARIKH	BUTIRAN	RUJUKAN	JURUAUDIT	CAWANGAN KEJURUTERAAN ELEKTRIK		CAWANGAN JALAN	 JABATAN KERJA RAYA MALAYSIA			NAMA PELANGGAN
			UNIT KESELAMATAN JALAN NO. LAPORAN AUDIT :	PENGARAH KANAN	PENGARAH PERUNDING REKABENTUK	PENGARAH KANAN KETUA PENOLONG PENGARAH KANAN (HOPT)	 KEMENTERIAN KERJA RAYA			BIL. HELAIAN:
				KETUA JURUTERA ELEKTRIK	JURUTERA ELEKTRIK PENGUASA					
				JURUTERA ELEKTRIK	PENOLONG JURUTERA ELEKTRIK					
PINDAAN							TARIKH:	SKALA: 1: 1500	BIL. LUKISAN:	


SCHEMATIC DRAWING FOR ROAD LIGHTING FEEDER PILLAR 1A




TARIKH	BUTIRAN	RUJUKAN	JURUAUDIT	CAWANGAN KEJURUTERAAN ELEKTRIK		CAWANGAN JALAN	 JABATAN KERJA RAYA MALAYSIA			NAMA PELANGGAN
			UNIT KESELAMATAN JALAN	PENGARAH KANAN	PENGARAH PERUNDING REKABENTUK		 KEMENTERIAN KERJA RAYA			
				KETUA JURUTERA ELEKTRIK	JURUTERA ELEKTRIK PENGUASA	PENGARAH KANAN				
				JURUTERA ELEKTRIK	PENOLONG JURUTERA ELEKTRIK	KETUA PENOLONG PENGARAH KANAN (HOPT)				
PINDAAN			NO. LAPORAN AUDIT :				BUTIRAN: SCHEMATIC DIAGRAM FOR FEEDER PILLAR (No.)			
							TARIKH:	SKALA: M.T.S.	BIL. LUKISAN:	BIL. HELAIAN:




TYPICAL CROSS-SECTION OF U5 AT EXISTING ROAD. (CH. 2000.00 TO CH. 2500.00)
SCALE : 1 : 40



TYPICAL CROSS SECTION OF JALAN DATUK KUMBANG



TYPICAL CROSS SECTION OF BRIDGE







TYPICAL CROSS-SECTION OF U5 AT NEW ROAD.

TARIKH	BUTIRAN	RUJUKAN	JURUAUDIT	CAWANGAN KEJURUTERAAN ELEKTRIK		CAWANGAN JALAN	 JABATAN KERJA RAYA MALAYSIA			NAMA PELANGGAN
			NO. LAPORAN AUDIT :	PENGARAH KANAN	PENGARAH PERUNDING REKABENTUK	PENGARAH KANAN	PROJEK:			 KEMENTERIAN KERJA RAYA
				KETUA JURUTERA ELEKTRIK	JURUTERA ELEKTRIK PENGUASA					
				JURUTERA ELEKTRIK	PENOLONG JURUTERA ELEKTRIK					
PINDAAN				KETUA PENOLONG PENGARAH KANAN (HOPT)		TARIKH: SKALA: BIL. LUKISAN:			BIL. HELAIAN:	
						N.T.S.				

CORBEL DETAIL & PIT DETAIL

Model Drawing No. 15J




LUKISAN TENDER





TARIKH	BUTIRAN	RUJUKAN	JURUAUDIT	CAWANGAN KEJURUTERAAN ELEKTRIK		CAWANGAN JALAN	JABATAN KERJA RAYA MALAYSIA		NAMA PELANGGAN
			UNIT KESELAMATAN JALAN	PENGARAH KANAN	PENGARAH PERUNDING REKABENTUK		PROJEK :		 KEMENTERIAN LUAR BANDAR DAN WILAYAH
				KETUA JURUTERA ELEKTRIK	JURUTERA ELEKTRIK PENGUASA	PENGARAH KANAN	BUTIRAN :	DETAIL CORBEL AND PIT AT BRIDGE	
				JURUTERA ELEKTRIK	PENOLONG JURUTERA ELEKTRIK	KETUA PENOLONG PENGARAH KANAN (HOPT)	TARIKH:	SKALA: NTS	
	PINDAAN		NO. LAPORAN AUDIT :				BIL. LUKISAN:		BIL. HELAIAN:

LEGEND:


Model Drawing No. 15K

SYMBOL	DESCRIPTION	QUANTITY
	OVERHEAD POLE	2 NOS.
	VERTICAL POLE	6 NOS.
	TYPE OF TRAFFIC SIGNAL HEAD	-
	TRAFFIC SIGNAL CONTROLLER (TSC)	1 NO.
	100 mm GI PIPE CLASS 'C'	300 METER
	LOOP DETECTOR	7 NOS.
	DETECTOR PIT (300 mm X 300 mm X 300mm)	4 NOS.
	CABLE PIT (450 mm X 450 mm X 450mm)	8 NOS.




PHASE A	PHASE B	PHASE C	PHASE D
			
THE ACTUAL PHASING / PHASE TIME DESIGN SHALL BE OBTAINED FROM TRAFFIC DESIGNER (JURUTERA PERUNDING FAJAR SDN. BHD.)			



SIGNAL HEAD LIGHT



* 1st ROAD LIGHTING POLE SHALL BE LOCATED WITHIN 3m FROM TRAFFIC SIGNAL POLE

TARIKH	BUTIRAN	RUJUKAN	JURUAUDIT	CAWANGAN KEJURUTERAAN ELEKTRIK		CAWANGAN JALAN	JABATAN KERJA RAYA MALAYSIA		NAMA PELANGGAN
			UNIT KESELAMATAN JALAN	PENGARAH KANAN	PENGARAH PERUNDING REKABENTUK		PROJEK:		 KEMENTERIAN KERJA RAYA
				KETUA JURUTERA ELEKTRIK	JURUTERA ELEKTRIK PENGUASA	PENGARAH KANAN	BUTIRAN: TRAFFIC SIGNAL LIGHT LAYOUT AT JUNCTION (No.)		
			NO. LAPORAN AUDIT :	JURUTERA ELEKTRIK	PENOLONG JURUTERA ELEKTRIK	KETUA PENOLONG PENGARAH KANAN (HOPT)	TARIKH:	SKALA: 1: 1500	BIL. HELAIAN:
	PINDAAN								






LEGEND	
ST	SILT TRAP
WT	WASH THROUGH
N	NOISE MONITORING
A	AIR QUALITY
W1	WATER QUALITY
○	CHECK DAM
—●—	SILT FENCE
—	EARTH DRAIN

TARIKH		BUTIRAN		RUJUKAN	JURUUKUR  UNIT UKUR TANAH CAW. PENGKALAN UDARA DAN MARITIM JABATAN KERJA RAYA MALAYSIA	CAWANGAN ALAM SEKITAR & TENAGA				CAWANGAN JALAN		 JABATAN KERJA RAYA MALAYSIA		PELANGGAN	
						1:1000	PENGARAH								
							JURUAUDIT		KETUA PENOLONG PENGARAH						
							JURUAUDIT KESELAMATAN JALAN		DIREKABENTUK:		DISEMAK:				
									DILUKIS:		DILULUSKAN:		KETUA PENOLONG PENGARAH KANAN (HOPT)		
PINDAAN					UKURAN					KETUA PENOLONG PENGARAH KANAN (HOPT)		ENVIROMENTAL PROTECTION WORK		KEMENTERIAN KEDAPARA MALAYSIA	
												TARIKH :		BIL. LUKISAN :	

GROUND TREATMENT SCHEDULE

[illegible]

TARIKH	BUTIRAN	RUJUKAN	NOT TO SCALE UKURAN	JURUUKUR	CAWANGAN KEJURUTERAAN GEOTEKNIK		CAWANGAN JALAN	 JABATAN KERJA RAYA MALAYSIA	 PELANGGAN KEMENTERIAN KERJA RAYA
					PENGARAH				
					JURUAUDIT	KETUA PENOLONG PENGARAH KANAN	PENGARAH		
						DIREKABENTUK:	DISEMAK:		
						DILUKIS:	DILULUSKAN:		
PINDAAN						KETUA PENOLONG PENGARAH KANAN (HOPT)	TARIKH:	BIL. LUKISAN:	
							GROUND TREATMENT SCHEDULE		




NOTES:


CONSISTENCY/RELATIVE DENSITY	
Cohesive Soil (N)	Non Cohesive Soil (N)
0 - 2 Very Soft	0 - 4 Very Loose
2 - 4 Soft	4 - 10 Loose
4 - 8 Medium Stiff	10 - 30 Medium Dense
8 - 15 Stiff	30 - 50 Dense
15 - 30 Very Stiff	50 < Very Dense
30 < Hard	


BOREHOLE PROFILE

CLAY
SILT
SAND
GRAVEL
GRANITE



TARIKH	BUTIRAN	RUJUKAN		JURUUKUR	CAWANGAN KEJURUTERAAN GEOTEKNIK	CAWANGAN JALAN	JABATAN KERJA RAYA MALAYSIA	PELANGGAN
					PENGARAH	PENGARAH		
					KETUA PENOLONG PENGARAH KANAN			
					DIREKABENTUK:	DISEMAK:		
					DILUKIS:	DILULUSKAN:		
					KETUA PENOLONG PENGARAH KANAN (HOPT)			
							LOCATION OF SOIL PROFILE ON PLAN AND LONGITUDINAL PROFILE	
							TARIKH:	BIL. LUKISAN:






ROAD SECTION
PLAN VIEW
SCALE N.T.S

LEGEND :-

- SG DEEP SETTLEMENT GAUGES
- IM INCLINOMETER
- SM SETTLEMENT MARKER
- PZ PIEZOMETER



TYPICAL CROSS SECTION FOR INSTRUMENTATION
SCALE N.T.S

TABLE 3 : INSTRUMENTATION SCHEDULES

CHAINAGE	FILL EMBANKMENT (m)	DEEP SETTLEMENT (DSG) GAUGE			SETTLEMENT MARKER (SM)		INCLINOMETER (IM)	
		LHS	C	RHS	LHS	RHS	LHS	RHS

TABLE 4: PROPOSED DATA COLLECTION SCHEDULE OF INSTRUMENTATION

DURATION	FREQUENCY
DURING FILLING WORKS UP TO SUBGRADE LEVEL	THE READING SHOULD BE RECORDED AFTER EACH CHANGE IN LOADING (EACH LAYER OF EMBANKMENT)
NEXT 2 WEEKS AFTER COMPLETION OF FILLING WORK	EVERY 3 DAYS
NEXT 4 WEEKS	1 TRIP / WEEK
NEXT 13 WEEKS	1 TRIP / 2 WEEKS

NOTES :

- ALL INSTRUMENTS SHALL BE IN ACCORDANCE TO THE SPECIFICATION AT LOCATIONS SPECIFIED IN TABLE 3. THE INSTRUMENTS SHALL BE ARRANGED AT LOCATIONS SUBJECT TO MINIMUM CONSTRUCTION ACTIVITIES AND OBSTRUCTION.
- PROCEDURE OF MONITORING AND FREQUENCIES OF THE INSTRUMENTS SHALL BE IN ACCORDANCE TO THE SPECIFICATION AND TABLE 4.
- PROPER PROTECTIONS APPROVED BY THE ENGINEER SHALL BE PROVIDED FOR ALL INSTRUMENTS.
- SHOULD ANY INSTRUMENT BE DAMAGED, ALL CONSTRUCTION ACTIVITIES IN THE VICINITY OF THE INSTRUMENT SHALL BE STOPPED UNTIL THE NECESSARY REMEDIAL WORKS HAVE BEEN SATISFACTORILY CARRIED OUT.
- THE METHOD STATEMENT FOR INSTALLATION OF INSTRUMENTS NEED TO BE SUBMITTED TO THE ENGINEER FOR APPROVAL PRIOR TO STARTING OF WORKS.
- SETTLEMENT PLATES ARE USED TO MEASURE SETTLEMENT TAKING PLACE BENEATH THE EMBANKMENT DURING AND AFTER CONSTRUCTION . THE BASE PLATE AND THE FIRST LENGTH OF ROD SHALL BE PLACED AS EARLY AS POSSIBLE DURING EARTHWORKS, PREFERABLY BEFORE ANY SIGNIFICANT FILLING (INCLUDING ANY DRAINAGE BLANKET).
- SETTLEMENT PLATE AND MARKERS SHALL BE MONITORED BY STANDARD LEVELLING TECHNIQUES. THE DATUM USED SHALL BE PREFERABLY REQUIRE ONLY ONE SET UP TO THE LEVEL AND LEVELLING SHALL BE CLOSED BACK TO THE APPROVED DATUM LOCATED ON FIRM GROUND.
- TEMPORARY BENCH MARK (TBM) SHALL SET ON STABLE GROUND OR AT EXISTING PILED STRUCTURE APPROVED BY ENGINEER.
- THE CONTRACTOR SHALL CEASE FILLING AND INFORM THE S.O SHOULD THE INSTRUMENT SHOW THE FOLLOWING OVER A ONE WEEK MONITORING PERIOD.

(i) $\frac{\text{CHANGE OF PORE WATER PRESSURE}}{\text{INCREASE IN EMBANKMENT PRESSURE}} > 0.7$

(ii) $\frac{\text{MAXIMUM SURFACE HEAVE}}{\text{MAXIMUM VERTICAL SETTLEMENT}} > 0.2$

TARIKH	BUTIRAN	RUJUKAN	NOT TO SCALE UKURAN	JURUUKUR	CAWANGAN KEJURUTERAAN JALAN & GEOTEKNIK			CAWANGAN JALAN		JABATAN KERJA RAYA MALAYSIA		PELANGGAN
					PENGARAH						KEMENTERIAN KERJA RAYA	
					JURUAUDIT	KETUA PENOLONG PENGARAH KANAN		PENGARAH	DETAIL OF INSTRUMENTATION			
						DIREKABENTUK:	DISEMAK:					
PINDAAN						DILUKIS:	DILULUSKAN:	KETUA PENOLONG PENGARAH KANAN (HOPT)	TARIKH:	BIL. LUKISAN:		